

**Subsurface Conditions Data Report
Haul Route and Borrow Areas 3 and 4
Third Runway Project
Sea-Tac International Airport
Seatac, Washington**



**Prepared for
HNTB**

**October 22, 2001
4978-52**

AR 052175



**Subsurface Conditions Data Report
Haul Route and Borrow Areas 3 and 4
Third Runway Project
Sea-Tac International Airport
Seatac, Washington**

Anchorage

Boston

Chicago

**Prepared for
HNTB**

Denver

**October 22, 2001
4978-52**

Fairbanks

**Prepared by
Hart Crowser, Inc.**

Jersey City

**Reese P. Hastings
Senior Associate**

**Joe N. Morrice
Senior Staff Hydrogeologist**

Juneau

Long Beach

Portland

Seattle

CONTENTS		<u>Page</u>
INTRODUCTION		1
PURPOSE AND SCOPE		1
GENERALIZED GEOLOGIC DESCRIPTION AND SUBSURFACE SOIL CONDITIONS		2
<i>Generalized Geologic Conditions</i>		2
<i>Subsurface Conditions</i>		3
<i>Generalized Hydrogeologic Regime</i>		5
<i>Hydrogeologic Conditions</i>		6
<i>Soil Infiltration Characteristics</i>		8
USE OF THIS REPORT		9
REFERENCES		11
TABLES		
1	Borrow Area 3 Water Level Data	
2	Borrow Area 4 Water Level Data	
3	Summary of Infiltration Tests	
FIGURES		
1	Site Location	
2	Site Exploration Plan - Borrow Areas 3 and 4	
3	Site Exploration Plan - Haul Route	
4	Hydrogeologic Cross Section A-A' - Borrow Areas 3 and 4	
5	Hydrogeologic Cross Section B-B' - Borrow Area 3	
6	Hydrogeologic Cross Section C-C' - Borrow Area 4	
7	Groundwater Elevation Contour Map - Shallow Regional Aquifer - Borrow Area 3	
8	Groundwater Elevation Contour Map - Borrow Areas 3 and 4	
APPENDIX A		
FIELD EXPLORATIONS METHODS AND ANALYSIS		
	<i>Explorations and Their Location</i>	A-1
	<i>The Use of Dual-Wall Percussion Hammer Drilling with Reverse Circulation</i>	A-2
	<i>The Use of Auger Borings</i>	A-3
	<i>Penetration Test Procedures</i>	A-3

CONTENTS (Continued)

Page

Groundwater Observation Well Installation Excavation of Test Pits

A-4
A-5

FIGURES

A-1	Key to Exploration Logs
A-2 through A-6	Boring Log A3-B8-98 through A3-B12-98
A-7 through A-11	Boring Log A3-B13-99 through A3-B17-99
A-12 through A-16	Boring Log A3-B-18-01 through A3-B22-01
A-17 through A-19	Boring Log A4-B4-98 through A4-B6-98
A-20 through A-24	Boring Log A4-B7-01 through A4-B11-01
A-25	Test Pit Log A4-TP1-01 through A4-TP3-01
A-26	Test Pit Log HR-TP1-01 and HR-TP2-01
A-27	Hand-Auger Boring Log HR-B1-01 through HR-B3-01

ATTACHMENT A-1 AGI FIGURES

AGI Soil Classification/Legend
AGI Boring Log A3-B1-93 and A3-B1-93
AGI Boring Log A3-B3-94 through A3-B7-94
AGI Boring Log A4-B1-94 through A4-B3-94

APPENDIX B LABORATORY TESTING PROGRAM

Soil Classification	B-1
Water Content Determinations	B-1
Grain Size Analysis (GS)	B-2
200-Wash (GS₂₀₀)	B-2

FIGURES

B-1	Unified Soil Classification (USC) System
B-2 through B-7	Grain Size Distribution Test Reports

CONTENTS (Continued)

Page

**APPENDIX C
BORROW AREA 3 PERCHED WATER-BEARING ZONE
SLUG TEST ANALYSIS**

Hydraulic Conductivity Testing (Slug Testing)

C-1

TABLE

C-1 Hydraulic Conductivity Calculations for Wells in Unconfined Aquifer,
Proposed Borrow Area 3

FIGURES

- C-1 Log of Normalized Drawdown vs. Fine for A3-B13-99
- C-2 Log of Normalized Drawdown vs. Fine for A3-B15-99
- C-3 Log of Normalized Drawdown vs. Fine for A3-B16-99
- C-4 Log of Normalized Drawdown vs. Fine for A3-B17-99

**SUBSURFACE CONDITIONS DATA REPORT
HAUL ROUTE AND BORROW AREAS 3 AND 4
THIRD RUNWAY PROJECT
SEA-TAC INTERNATIONAL AIRPORT
SEATAC, WASHINGTON**

INTRODUCTION

This data report presents technical documentation of subsurface conditions, laboratory testing, and relevant geotechnical and hydrogeologic field testing of two Third Runway Borrow Areas and the associated Haul Route. A previous data report (Hart Crowser 1999) documented conditions at Borrow Areas 1, 3, and 4. The current report presents additional data collected since that time and supersedes in these areas the 1999 report for Borrow Areas 3 and 4, as well as provides information about the proposed Haul Route (Hart Crowser 2001). Borrow Areas 3 and 4 have been identified as sources of borrow materials to be used as construction fill for the Third Runway Embankment Project. These borrow areas are located south of the Sea-Tac International Airport, in SeaTac, Washington (refer to Figure 1, Vicinity Map).

Figure 1 shows the general area where we have performed geotechnical and hydrogeologic explorations for this study. Explorations and testing within the borrow areas and along the haul route are characterized in greater detail on Figures 2 and 3. Cross sections showing inferred geologic and hydrogeologic conditions are provided on Figures 4 through 6. Water level data and groundwater elevation contours for the Regional Shallow Aquifer are shown on Figure 7. Groundwater contours for the Perched Water-Bearing Zone in Borrow Areas 3 and 4 are shown on Figure 8.

We have organized this report into several sections. The main text starts with a discussion of site geology and is followed by a discussion of the hydrogeologic conditions and near-surface soil infiltration characteristics obtained from explorations conducted to date. Appendices A through C follow the main text and present results of our subsurface explorations, laboratory data, and hydrogeologic data, respectively, from this and previous investigations.

PURPOSE AND SCOPE

This report presents data collected on soil, glacially deposited materials, and groundwater conditions at Borrow Areas 3 and 4 and along the proposed Haul Route. The purpose of this report is to supplement data presented previously

(Hart Crowser 1999) identifying suitable embankment construction materials, and to support the design and development of the borrow areas and haul route.

The scope of Hart Crowser's work included completion of borings and test pits, the installation of monitoring wells, measurement of groundwater elevations, and performance of infiltration tests. The following paragraphs summarize work completed since the 1999 data report was issued.

Five additional borings were completed at Borrow Area 3 in June 2001. One boring (A3-B22-01) was completed as a monitoring well. The other four borings (A3-B18-01 through A3-B21-01) were used to perform falling head percolation tests and were then abandoned.

Five additional borings and three test pits were completed at Borrow Area 4 in June 2001. Dual-ring infiltrometer tests were performed in each of the test pits. A falling head percolation test was performed at boring A4-B09-01, which was then abandoned. Borings A4-B08-01 and A4-B10-01 were completed as monitoring wells in the perched water-bearing zone. Borings A4-B07-01 and A4-B11-01 were completed as monitoring wells in the Shallow Regional Aquifer.

Three hand-auger borings and two test pits were completed along the Haul Route in June 2001. Falling head percolation tests were performed in the borings and dual-ring infiltrometer tests were performed in the test pits.

GENERALIZED GEOLOGIC DESCRIPTION AND SUBSURFACE SOIL CONDITIONS

This section provides a description of the geologic and subsurface conditions of soils and glacial deposits within the areas shown on Figures 2 and 3, based on our explorations at the site and explorations by others. Previous studies of the local geologic and hydrologic conditions at Borrow Areas 3 and 4 have been accomplished by AGI Technologies (AGI 1995 and 1996).

Generalized Geologic Conditions

The most recent investigations did not result in any new interpretation of generalized geologic conditions in the area. The following findings remain unchanged from the 1999 data report.

The site is located on the Des Moines Drift Plain in the Puget Sound Lowland. Glacial soils have been deposited and extensively reworked by glacial episodes, the most recent being the Vashon Stade of Puget Sound glaciation.

In summary, the following geologic units have been identified at Borrow Areas 3 and 4:

- Fill (variably graded, silt, sand, and gravel);
- Alluvium (peats and silts; and medium dense, fine to medium sand);
- Recessional Outwash (primarily silty, sand and gravel, and/or sandy silt or sandy clay);
- Glacial Till (clayey, silty sand and gravel);
- Advance Outwash (non-silty to silty sand and gravel);
- Lawton Clay (very stiff to hard silt and clay); and
- Puyallup Formation (fine sand and silty sand).

Surficial soils in Borrow Areas 3 and 4 have been mapped as glacial till with localized surficial deposits of recessional outwash. Our explorations within Borrow Areas 3 and 4 suggest that these areas are part of a north-south trending ridge known as a drumlin.

Subsurface Conditions

Our interpretation of subsurface conditions at Borrow Areas 3 and 4 did not change based on new data acquired since 1999. The following section presents text from the 1999 data report, with additional discussion of conditions encountered along the Haul Route.

Subsurface soil and hydrogeologic conditions interpreted from data collected and observations made during explorations at the site, and previously mentioned AGI studies, formed the basis for the information contained within this report. Variations between explorations may occur as irregularities in gradation, moisture content, and density/consistency of soils at the site. The nature and extent of these variations may not become evident until construction. Exploration boring logs for the borrow areas and haul route are presented in Appendix A.

Subsurface conditions encountered in Borrow Areas 3 and 4 (shown on Figures 4 through 6) consist of a thin mantle of recessional outwash over glacial till, which in turn overlies advance outwash materials. These glacial sedimentary sequences overlie earlier deposits of Vashon glacial till, which overlie the

Puyallup Formation. Figure 4 is a generalized north-south cross section through Borrow Areas 3 and 4. Figures 5 and 6 are northwest-southeast and west-east cross sections through Borrow Areas 3 and 4, respectively. Detailed descriptions of the materials we encountered are provided below.

Subsurface conditions encountered along the Haul Route consisted of topsoil and fill over silt, possibly a post-glacial lacustrine deposit. These explorations were less than 10 feet deep. Explorations from the South Aviation Support Area (SASA) study (FAA 1994) located approximately 500 feet to the east indicated a thickness for the silt unit of approximately 10 feet.

Topsoil. This soil was not consistently encountered in our explorations. Typically, the topsoil consists of a loose mixture of silt and sand with roots and other organic material. Topsoil is generally 1/2 to 1 foot thick where encountered. Many of the surficial soils at the site appear to be glacial deposits at different stages of weathering. This is further discussed in the **Recessional Outwash and Glacial Till** sections below.

Fill Soils. Fill soils were encountered in both proposed borrow areas and along the haul route, typically associated with paved streets, or general grading associated with past use of the sites. Fill soils are generally loose to medium dense, variable mixtures of silt, sand, and gravel. The density and granular nature of the fill materials resemble the recessional outwash deposits and the fill is sometimes difficult to distinguish from the outwash.

Alluvial Deposits. These sediments occur in the low-lying areas and generally consist of soft/loose, moist to wet, interlayered silt, sand, and peat.

Recessional Outwash. This material is generally slightly silty to silty, slightly gravelly to gravelly sand. Recessional outwash overlies the glacial till, or advance outwash where the glacial till has been eroded. Recessional outwash forms a thin veneer over much of Borrow Areas 3 and 4, generally measuring less than 5 feet thick. Thicker deposits occur in southern portions of Borrow Area 3 which show historical signs of borrow development activities possibly related to previous airport construction.

Where recessional outwash is located at the ground surface, it is in a weathered condition. This layer may become colluvium where deposits are on sufficiently sloping ground.

Glacial Till. The till comprises the predominant glacially overridden unit underlying the surficial materials discussed above. This material is generally

comprised of a dense, slightly gravelly to gravelly, silty to very silty sand. The gradation of the till varies both vertically and laterally.

In general, glacial till differs from the overlying recessional outwash by having a higher silt content and much higher density. The top of the glacial till is generally within 5 feet of the ground surface at each of the borrow areas, except in the southern portions of Borrow Area 3. The drumlin feature noted in Borrow Areas 3 and 4 is dominated by glacial till within the central and northern portions of Borrow Area 3. Glacial till is present throughout most of Borrow Area 4. Some weathering has been noted near the surface of the glacial till in explorations in each borrow area.

Advance Outwash Sand. This material is generally dense to very dense, slightly silty, slightly gravelly to gravelly sand. In general, the advance outwash can be distinguished from the glacial till by lower silt content. However, observations at the borrow areas where this material was encountered suggest that some areas of advance outwash may be silty. It occurs beneath the glacial till noted in each borrow area.

Lawton Silt/Pre-Vashon Deposits. The hard silt interpreted to be part of these geologic units in previous studies were not encountered in our explorations, but would likely be encountered at greater depths. These hard silts may be laminated or contain planes of separation (partings). Furthermore, these silt deposits are typically reported to be relatively plastic and are often slickensided (i.e., showing evidence of previous deformation).

Generalized Hydrogeologic Regime

The most recent investigations did not result in any new interpretation of generalized hydrogeologic conditions in the area. The following text is unchanged from the 1999 data report.

On a regional scale, the glacial deposits at depth beneath Borrow Areas 3 and 4 and the Haul Route consist of "relatively permeable" slightly silty to silty sands and gravels, with intervening layers of low-permeability glacial till and predominantly fine-grained sediments (e.g., silt and gravelly, sandy silt). Regional aquifers (indicated below in **bold type**) occur within the glacially derived, below the proposed borrow areas (AGI 1996):

- Fill, Alluvium, Vashon Recessional Outwash – Perched Water-Bearing Zones
- Vashon Till – Aquitard
- Vashon Advance Outwash – **Shallow Regional Aquifer**
- Lawton Clay – Aquitard

- "Third" Coarse-Grained Deposit - Intermediate Regional Aquifer
- Puyallup Formation - Aquitard
- "Fourth" Coarse-Grained Deposit - Deep Regional Aquifer

Hydrogeologic Conditions

Borrow Areas 3 and 4 and the Haul Route are located within the Des Moines Creek drainage. The glacial till and the advance outwash act as semi-perching layers, allowing some portion of local precipitation to infiltrate down to the underlying Advance Outwash, which is typically more permeable. The Advance Outwash contains a water table known as the Shallow Regional Aquifer, which discharges to Des Moines Creek, and via underflow, into Puget Sound and the Green River valley (AGI 1996).

Groundwater elevation data were collected from explorations in Borrow Areas 3 and 4, which identified a perched water-bearing zone overlying the shallow regional aquifer. Slug testing was performed in Borrow Area 3 to obtain data for estimating hydraulic conductivity values to evaluate the perched water-bearing zone characteristics as they relate to the wetlands and borrow material development. These data and analyses are discussed below. Water levels in these borrow areas vary over time, as indicated in Tables 1 and 2.

The borrow areas are generally situated within the recessional outwash and glacial till deposits sequences, and extend into the upper part of the advance outwash, above the water table referred to as the Shallow Regional Aquifer. Figures 5 and 6 are conceptual cross sections through the Borrow Areas and depict the local perched water-bearing zone and the underlying Shallow Regional Aquifer.

Borrow Areas 3 and 4. Borrow Areas 3 and 4 are located above the Shallow Regional Aquifer. Soil borrow excavations are anticipated to encounter local perched water-bearing zones in Borrow Area 3. Measured groundwater levels and monitoring well elevation data are summarized in Tables 1 and 2.

Our interpretation of groundwater conditions is based on current observations as well as information previously reported (AGI 1995). The reported information included water level observations in two wells previously drilled by AGI which could not be located in the field at the time of our work, as well as notations of wet soils (indicating perched water-bearing zones) in the AGI boring logs.

Hart Crowser installed thirteen monitoring wells in Borrow Areas 3 and 4 in 1998 and 1999, and an additional five monitoring wells in 2001. These wells

were used along with observations in four pre-existing wells to improve definition of groundwater conditions. Limited information previously available suggested the borrow areas might be underlain by groundwater with a relatively steep sloping gradient to south (AGI 1995). Current observations based on the available wells indicate a somewhat different picture—a relatively flat perched water-bearing zone in the north part of Borrow Area 3 and in Borrow Area 4 overlies the relatively flat water table in the Shallow Regional Aquifer.

Slug tests were performed in five wells at Borrow Area 3 to estimate the hydraulic conductivity of the perched groundwater zone; the test plot-graphs are presented on Figures C-1 through C-4 in Appendix C.

Haul Route. Groundwater was not observed in any of the explorations along the Haul Route. Seepage was noted in HR-TP02-01 at a depth of 6.5 feet. Explorations from the SASA study near Des Moines Creek encountered groundwater at depths ranging from 5 to 12 feet, with depths generally increasing as the land slopes upward away from the creek.

Groundwater Flow Mapping

Groundwater levels for Borrow Areas 3 and 4 were measured in 22 monitoring wells. Groundwater elevations are contoured on Figure 7 for the Shallow Regional Aquifer, illustrating groundwater flow directions. Groundwater elevations for the perched water-bearing zone are contoured on Figure 8.

Shallow Regional Aquifer. Continuous groundwater flow through Borrow Areas 3 and 4 occurs in the Shallow Regional Aquifer, which underlies both areas and is fed by infiltration from the surface and discontinuous overlying perched water-bearing zones. Groundwater from this aquifer can be seen on Figure 7 to flow eastward toward Des Moines Creek.

Perched Water-Bearing Zone. The perched water-bearing zone apparently extends west of Borrow Areas 3 and 4, based on local surface topography and is recharged by infiltration of rainfall on the higher ground to the west. The resulting perched groundwater flow direction is generally from the west, toward the south and southeast into Borrow Area 3. The overall flow pattern is also affected locally by outward radial flow from the high ground in Borrow Area 4. The perched water-bearing zone appears to pinch out to the north, where the perching horizon gradually rises and intersects ground surface. Approximate groundwater elevation contours for the perched water-bearing zone are illustrated on Figure 8.

Soil Infiltration Characteristics

Infiltration characteristics of soils beneath the locations of proposed stormwater retention and infiltration facilities were evaluated at Borrow Areas 3 and 4 and the Haul Route. Infiltration rates were estimated at each site using a combination of double-ring infiltrometer tests (ASTM Method D 3385, 2000) and falling head percolation tests (EPA 1980).

Infiltration tests were performed at the bottom of test pits excavated using a backhoe at locations where the testing horizon was less than 5 feet deep. Falling head percolation tests were performed in borings drilled with a hollow-stem auger drill rig at locations where the testing horizon was greater than 5 feet deep, or in shallow hand-augered borings where site disturbance resulting from a backhoe excavation was deemed unacceptable (e.g., Tye Golf Course). Results of infiltration tests at the borrow areas and the Haul Route are shown in Table 3.

Borrow Area 3

Four falling head percolation tests were performed in borings A3-B18-01 through A3-B21-10 in the location of a proposed storage and infiltration pond at Borrow Area 3 (Figure 2). The targeted test horizon was at an elevation of 227 feet. Subsurface materials at the site consisted of slightly silty to silty, fine to medium sand from just below ground surface to depths of up to 39 feet (approximate elevation 205 feet). In these four borings the sand extends at least 5 feet below elevation 227 feet. Water levels in the vicinity of the infiltration tests range from elevations of about 210 to about 220 feet.

Measured infiltration rates at Borrow Area 3 range from 0.17 to 1.1 minutes/inch, as shown in Table 3. These rates are consistent with the sandy material encountered at this site.

Borrow Area 4

Three double-ring infiltrometer tests were performed in test pits A4-TP1-01 through A4-TP3-01 in the location of a proposed storage and infiltration pond at Borrow Area 4 (Figure 2). A falling head percolation test was attempted at boring A4-B9-01, but failed due to seepage of water into the bottom of the boring. Test elevations ranged from 290 to 296 feet, with a targeted elevation of 292 feet. Each test pit was extended 5 feet below the test horizon to log the underlying. These materials consisted primarily of silt with varying amounts of sand or gravel and are described as till-like. Groundwater seepage was not noted in any of the test pits; however, groundwater elevations from shallow wells in the vicinity indicate groundwater levels as high as 293.7 feet.

Measured infiltration rates at Borrow Area 4 were much lower than those at Borrow Area 3, ranging from 44 to 170 minutes/inch. These rates are consistent with the till-like sandy silt encountered at this site.

Haul Route

Two double-ring infiltrometer tests were performed in test pits (HR-TP1-01 and HR-TP2-01) along the Haul Route, one each at the location of two proposed ponds (Figure 3). Additionally, three falling head percolation tests were performed in hand-auger borings (HR-B1-01 through HR-B3-01) along a proposed infiltration trench following the Haul Route road alignment. Hand-auger borings were used at these locations to minimize disturbance to the Tye Golf Course. Groundwater was not encountered in explorations at this site; however, seepage was noted at a depth of 6.5 feet (approximate elevation 246 feet) at HR-TP2-01.

Ponds

Soils encountered at the two pond locations consisted of either topsoil or fill over non-sandy to slightly sandy silt. The silt extended past the infiltration testing horizon an additional 3 to 6 feet to the bottom of each exploration. Measured infiltration rates were very low, ranging from 440 to 480 minutes/inch.

Road Alignment

Soils encountered along the trace of the proposed haul route consisted of approximately 1 foot of silty topsoil over sandy silt. Tests were performed immediately below the topsoil layer. Field personnel were only able to advance the hand-auger borings and collect soil samples for logging between 1 and 3 feet below the testing horizon. Measured infiltration rates ranged from 10.5 to 120 minutes/inch; however, these rates are likely overestimates of longer term infiltration rates due to the presence of the tighter gray silt layer at a depth of approximately 3 feet throughout the site.

USE OF THIS REPORT

Hart Crowser completed this work in general accordance with our change order dated August 3, 2001, and our contract with HNTB referred to as Amendment 22. This report is for the exclusive use of HNTB, the Port of Seattle, and their design consultants for specific application to the Third Runway project and site. We completed this study in accordance with generally accepted geotechnical/hydrogeologic practices for the nature and conditions of the work

completed in the same or similar localities, at the time the work was performed.
We make no other warranty, express or implied.

F:\docs\jobs\497852\BA3&4DataReport.doc

REFERENCES

AGI Technologies 1995. Borrow Source Study, Proposed New Runway, Seattle-Tacoma International Airport, SeaTac, Washington. Draft Report prepared for HNTB, April 3, 1995.

AGI Technologies 1996. Appendix Q-A, Baseline Groundwater Study, Final Environmental Impact Statement, Proposed Master Plan Update, Sea-Tac International Airport, SeaTac, Washington, January 3, 1996.

ASTM 2000. Double Ring Infiltrometer Test, ASTM Method D 3385, Annual Book of ASTM Standards, Soil and Rock (1): D 420-D5799.

EPA 1980. EPA Falling Head Percolation Test Procedure, Design Manual - Onsite Wastewater Treatment and Disposal Systems, U.S. Environmental Protection Agency.

FAA 1994. South Aviation Support Area (SASA), Final Environmental Impact Statement, Technical Appendices. Federal Aviation Administration, Seattle Airports District Office. March 1994.

Hart Crowser 1999. Subsurface Conditions, Data Report, Borrow Areas 1, 3, and 4, Sea-Tac Airport Third Runway. Prepared for HNTB and the Port of Seattle. September 24, 1999.

Hart Crowser 2001. Conceptual Borrow Material Development and Reclamation Plan - Borrow Areas 3 and 4, Sea-Tac International Airport. Prepared for the Port of Seattle. August 15, 2001.

F:\docs\jobs\497852\BA3&4DataReport.doc

Table 1 - Borrow Area 3 Water Level Data

	A3-B3-94		A3-B7-94		A3-B8-98		A3-B9-98		A3-B10-98		A3-B11-98		A3-B12-98	
	Depth* in Feet	Elevation in Feet	Depth* in Feet	Elevation in Feet	Depth* in Feet	Elevation in Feet	Depth* in Feet	Elevation in Feet	Depth* in Feet	Elevation in Feet	Depth* in Feet	Elevation in Feet	Depth* in Feet	Elevation in Feet
Top of Monument	-0.90	248.94	NOT SURVEYED		-0.35	283.22	-0.55	272.83	-0.30	321.44	-0.75	350.90	-0.40	244.32
Measuring Point	0.00	248.04	0.00	317.0	0.00	282.87	0.00	272.28	0.00	321.14	0.00	350.15	0.00	243.92
Ground Level*	1.84	246.2	2.00	315.0	2.37	280.5	2.28	270.0	2.54	318.6	1.75	348.4	2.82	241.1
Top of Screen*	38.8	209.2	94.5	222.5	71.8	211.1	53.8	218.5	87.5	233.6	133.0	217.2	27.6	216.3
Bottom of Well*	50.8	197.2	104.5	212.5	82.3	200.8	64.2	208.1	97.8	223.3	143.3	206.9	37.9	206.0
Date: 12/28/94	35.1	211.1	87.3	227.7	--	--	--	--	--	--	--	--	--	--
1/26/1995	33.8	212.4	86.6	228.4	--	--	--	--	--	--	--	--	--	--
(ATD)														
5/15/1998	--	--	--	--	51.09	231.78	41.25	231.03	88.16	232.98	120.55	229.60	20.03	223.89
5/22/1998	29.94	218.10	--	--	51.16	231.71	41.15	231.13	88.16	232.98	120.35	229.80	20.21	223.71
6/2/1998	30.02	218.02	--	--	51.17	231.70	41.11	231.17	88.13	233.01	120.39	229.76	20.39	223.53
4/23/1999														
4/27/1999														
5/5/1999														
6/14/1999	28.28	219.76	--	--	50.13	232.74	39.69	232.59	87.01	234.13	119.32	230.83	18.71	225.21
7/13/1999	29.10	218.94	--	--	49.66	232.21	40.13	232.15	88.79	232.35	120.08	230.09	19.65	224.27
8/13/1999	29.93	218.11	--	--	50.48	232.39	40.89	231.39	89.50	231.64	120.79	229.36	20.63	223.29
9/14/1999	29.71	218.33	--	--	51.03	231.84	41.21	231.07	88.67	232.47	120.93	229.22	21.57	222.35
10/13/1999	31.40	216.64	--	--	51.80	231.07	41.82	230.46	89.09	232.05	121.27	228.88	22.28	221.64
11/11/1999	31.96	216.08	--	--	52.66	230.21	41.92	230.36	88.82	232.52	120.14	230.01	22.70	221.22
12/10/1999	31.96	216.08	--	--	52.27	230.60	41.99	230.29	88.35	232.79	120.51	229.64	21.63	222.28
1/12/2000	30.09	217.95	--	--	--	--	41.30	230.98	87.57	233.57	119.71	230.44	20.45	223.47
2/15/2000	30.54	217.50	--	--	51.15	231.72	41.23	231.05	87.60	233.54	119.75	230.40	19.88	224.04
3/13/2000	29.78	218.26	--	--	50.53	232.34	40.44	231.64	87.18	233.96	119.35	230.80	19.20	224.72
4/12/2000	29.20	218.84	--	--	50.5	232.37	40.69	231.59	87.56	233.58	119.78	230.37	19.26	224.66
5/10/2000	29.57	218.47	--	--	50.95	231.92	40.97	231.31	87.89	233.25	120.12	230.03	19.87	224.05
6/2/2000	30.38	217.66	--	--	52.01	230.86	41.94	230.34	89.09	232.05	121.34	228.81	20.81	223.11
7/11/2000	30.83	217.21	--	--	52.74	230.13	42.47	229.81	89.63	231.51	121.88	228.27	21.37	222.55
10/13/2000	33.16	214.88	--	--	56.16	226.71	44.60	227.68	91.10	230.04	123.27	226.88	23.69	220.23
1/23/2001	35.00	213.04	--	--	56.77	226.10	44.96	227.32	90.99	230.15	123.10	227.05	24.14	219.78
5/3/2001	35.48	212.56	--	--	55.1	227.77	43.07	229.21	88.96	232.18	121.11	229.04	23.09	220.83
6/01 (ATD)	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Itelics = Estimated
 Depth* All depths are below measuring point (NOT below the ground surface)
 -- indicates data not available.

Table 1 - Borrow Area 3 Water Level Data

	A3-B13-99		A3-B14-99		A3-B15-99		A3-B16-99		A3-B17-99		A3-B22-01	
	Depth* In Feet	Elevation In Feet	Depth* In Feet	Elevation In Feet	Depth* In Feet	Elevation In Feet	Depth* In Feet	Elevation In Feet	Depth* In Feet	Elevation In Feet	Depth* In Feet	Elevation In Feet
Top of Monument	-0.31	286.66	-0.28	293.28	-0.26	303.28	-0.61	346.63	-0.46	304.86	--	--
Measuring Point	0.00	286.35	0.00	293.00	0.00	303.02	0.00	346.02	0.00	304.38	0.00	245.87
Ground Level*	1.5	284.9	2.5	290.5	3.3	299.7	2.0	344.0	1.8	302.6	2.07	243.6
Top of Screen*	54.5	231.9	37.5	255.5	22.3	280.7	55.0	291.0	18.3	286.1	31.07	214.8
Bottom of Well*	59.5	226.9	42.5	250.5	27.3	275.7	60.0	286.0	23.3	281.1	41.07	204.6
Date:												
1/26/1995	--	--	--	--	--	--	--	--	--	--	--	--
(ATD)												
5/15/1998	54.5	231.85	38.0	255.00	21.5	281.52	51.0	295.02	18.0	286.38	--	--
5/22/1998												
6/2/1998												
4/23/1999	54.65	231.70	37.75	255.25	21.81	281.21	50.6	295.42	18.25	286.13	--	--
4/27/1999	54.89	231.66	37.73	255.27	21.44	281.56	50.65	295.37	18.37	286.01	--	--
5/5/1999	54.87	231.48	37.87	255.13	21.68	281.36	50.76	295.26	18.59	285.79	--	--
6/14/1999	55.52	230.83	38.60	254.40	22.28	280.74	51.23	294.79	19.37	285.01	--	--
7/13/1999	55.94	230.41	39.01	253.99	22.85	280.17	51.82	294.20	19.86	284.50	--	--
8/13/1999	56.45	229.90	39.23	253.77	23.41	279.61	52.54	293.48	20.43	283.95	--	--
8/14/1999	57.08	229.27	38.08	254.92	23.88	279.14	53.16	292.86	20.97	283.41	--	--
10/13/1999	57.79	228.56	40.41	252.59	24.37	278.65	53.79	292.23	21.59	282.79	--	--
11/1/1999	58.71	227.64	41.05	251.95	24.62	278.40	54.23	291.79	22.02	282.36	--	--
12/10/1999	59.31	227.04	39.96	253.04	23.72	279.30	54.76	291.26	22.15	282.23	--	--
1/12/2000	58.87	227.48	39.39	253.61	23.40	279.82	54.78	291.24	21.61	282.77	--	--
2/15/2000	58.51	227.84	38.59	254.41	22.88	280.14	54.85	291.37	20.76	283.62	--	--
3/13/2000	58.02	228.33	38.35	253.85	22.38	280.64	54.20	291.82	19.90	284.48	--	--
4/12/2000	57.53	228.82	39.60	253.40	22.99	280.03	53.97	292.05	20.19	284.19	--	--
5/10/2000	57.87	228.48	40.11	252.99	23.43	279.59	53.92	292.10	20.82	283.76	--	--
6/2/2000	58.69	227.66	40.61	252.39	23.90	279.12	54.33	291.69	21.34	283.04	--	--
7/11/2000	59.12	227.23	40.92	252.06	24.21	278.81	54.51	291.51	21.71	282.67	--	--
10/13/2000	dry	dry	dry	dry	25.27	277.75	55.43	290.59	dry	dry	--	--
1/23/2001	dry	dry	40.74	252.26	25.01	278.01	56.42	289.60	dry	dry	--	--
5/3/2001	dry	dry	40.64	252.36	24.94	278.08	56.90	289.12	dry	dry	--	--
6/01 (ATD)	--	--	--	--	--	--	--	--	--	--	35.0	208.6

AR 052192

Table 2 - Borrow Area 4 Water Level Data

	A4-B1-94	A4-B2-94	A4-B4-98	A4-B5-98	A4-B6-98	A4-B7-91	A4-B9-01	A4-B10-01	A4-B11-01
	Depth: Elevation In Feet	Depth: Elevation In Feet	Depth: Elevation In Feet	Depth: Elevation In Feet	Depth: Elevation In Feet	Depth: Elevation In Feet	Depth: Elevation In Feet	Depth: Elevation In Feet	Depth: Elevation In Feet
Top of Monument	-0.50 392.84	NOT SURVEYED	-0.35 395.71	-0.30 371.26	-0.26 401.48	-	-	-	-
Measuring Point	0.00 392.34	0.00 345	0.00 395.36	0.00 370.96	0.00 401.22	0.00 306.83	0.00 310.22	0.00 297.54	0.00 297.13
Ground Level*	1.94 390.4	2.00 343	2.36 383.0	2.66 368.3	2.72 398.5	2.43 304.4	1.92 306.3	2.14 295.4	1.63 296.5
Top of Screen*	109.44 282.90	12 337	97.86 297.50	72.86 298.10	118.52 282.70	74.43 232.40	16.42 293.80	7.14 280.40	63.63 233.50
Bottom of Well*	119.44 272.90	22 323	108.06 277.30	83.11 287.85	128.72 272.50	84.43 222.40	26.42 283.60	17.14 280.40	73.63 223.50
Date:	(ATD) 12/28/94 12/28/95	6.5 336.5 8.9 333.1 10.9 332.1	-	-	-	-	-	-	-
			97.8 285.20	5.3 383.00	104.3 294.20	-	-	-	-
5/15/1998	-	-	93.28 282.07	80.67 280.29	107.37 283.85	-	-	-	-
5/22/1998	100.98 291.36	-	92.96 292.36	80.43 280.53	106.92 284.30	-	-	-	-
6/2/1998	100.70 281.84	-	90.71 284.65	78.65 282.31	104.97 286.25	-	-	-	-
6/15/1998	-	-	91.09 284.27	78.80 282.16	105.23 285.99	-	-	-	-
7/13/1998	-	-	91.42 293.94	79.08 291.88	105.47 285.75	-	-	-	-
8/13/1998	-	-	91.82 293.54	79.28 291.66	105.60 285.42	-	-	-	-
8/14/1998	-	-	92.27 293.09	79.42 291.54	106.17 285.05	-	-	-	-
10/13/1998	-	-	92.60 292.76	79.75 291.21	106.61 284.61	-	-	-	-
11/1/1999	100.20 282.14	-	93.13 292.23	Dry	106.07 284.35	-	-	-	-
12/10/1999	-	-	93.48 291.88	80.56 280.40	107.15 284.07	-	-	-	-
1/12/2000	-	-	93.71 291.65	Dry	107.35 283.67	-	-	-	-
2/15/2000	101.10 291.24	-	93.56 291.78	80.72 280.24	107.23 283.99	-	-	-	-
3/13/2000	101.03 291.31	-	93.55 291.81	80.70 280.26	107.22 284.00	-	-	-	-
4/12/2000	101.07 291.27	-	93.46 291.90	80.69 280.27	107.21 284.01	-	-	-	-
5/10/2000	101.01 291.33	-	93.34 292.02	80.62 280.34	107.17 284.05	-	-	-	-
6/21/2000	100.96 291.38	-	93.79 291.57	dry	107.44 283.78	-	-	-	-
7/11/2000	100.95 291.39	-	94.52 290.84	dry	108.01 283.21	-	-	-	-
10/13/2000	101.21 291.13	-	95.46 289.90	dry	108.90 282.32	-	-	-	-
1/23/2001	101.67 290.67	-	95.93 289.43	dry	109.34 281.88	-	-	-	-
5/3/2001	102.64 289.70	-	-	-	-	-	-	-	-
6/01 (ATD)	-	-	-	-	-	73.5 230.90	17.5 280.80	dry	66 229.50
6/28/2001	-	-	-	-	-	74.47 232.36	16.49 283.73	dry	55.21 241.92
7/31/2001	-	-	-	-	-	75.50 231.33	16.97 283.25	dry	55.50 241.63

Items = Estimated
 Depth* All depths are below measuring point (NOT below the ground surface) - except ATD
 - Indicates data not available.

**Table 3 - Summary of Infiltration Tests
Borrow Areas 3 and 4 and the Haul Route**

Borrow Area 3

Boring Number	Ground Surface Elevation in Feet	Boring Depth in Feet	Test Elevation in Feet	Infiltration Rate in minutes/inch
A3-B18-01	240.20	13 + 6.5	227	0.17
A3-B19-01	237.99	11 + 4.5	227	1.1
A3-B20-01	247.27	20 + 5.5	227	0.21
A3-B21-01	245.18	18 + 7.5	227	0.28

Borrow Area 4

Boring Number	Ground Surface Elevation in Feet	Boring Depth in Feet	Test Elevation in Feet	Infiltration Rate in minutes/inch
A4-B09-01	304.78	13 + 6	292	NM

Test Pit Number	Ground Surface Elevation in Feet	Test Pit Depth in Feet	Test Elevation in Feet	Infiltration Rate in minutes/inch
A4-TP01-01	299.76	4 + 5	296	44
A4-TP02-01	294.21	4 + 5	290	140
A4-TP03-01	294.17	4 + 5	290	170


Haul Route

Hand-Auger Boring Number	Ground Surface Elevation in Feet	Boring Depth in Feet	Test Elevation in Feet	Infiltration Rate in minutes/inch
HR-B01-01	252	1 + 2.6	251	10.5
HR-B02-01	250	1 + 3	249	14
HR-B03-01	250	1 + 1	249	120

Test Pit Number	Ground Surface Elevation in Feet	Test Pit Depth in Feet	Test Elevation in Feet	Infiltration Rate in minutes/inch
HR-TP01-01	256	6 + 3	250	480
HR-TP02-01	252	4 + 6	248	440

NM - Not Measured. Slow seepage into the bottom of the boring invalidated testing. Exploration depths indicate the depth at which infiltration testing was performed, plus the additional depth drilled for soil logging.

Site Location Map




497852/497852A.cdf

Note: Base map prepared from USGS 7.5 minute quadrangle maps of Seattle South Washington revised 1995

HARTCROWSER
 J-4978-52 10/01
 Figure 1

AR 052195

**Site Exploration Plan
Borrow Areas 3 and 4**



Notes:
 1) Base map prepared from drawing provided by HNTB entitled "L_topo.dwg", dated April 4, 2001.
 2) Field information prepared from drawing provided by Parometrix entitled, "w_022001.dwg", dated February 20, 2001.
 3) Refer to Figures 4 through 6 for Cross Sections.




Exploration Location and Number

- A3-91-03 Boring with Observation Well (Hart Crowser)
- A3-91-01 Boring (Hart Crowser)
- A3-91-04 Boring with Observation Well (AGI)
- A3-91-05 Boring (AGI)
- A4-TP1-01 Test Pit (Hart Crowser)

AA → Cross Section Location and Designation

Site Exploration Plan
Haul Route



Notes:
 1) Base map prepared from drawing provided by HNTB entitled "x_topo.dwg", dated April 4, 2001.
 2) Wetland delineation prepared from drawing provided by Parametrix entitled, "W_022001.dwg", dated February 20, 2001.



Exploration Location and Number

- HR-TP1-01 Test Pit (Hart Crowser)
- HR-B1-01 Hand Auger Boring (Hart Crowser)




Hydrogeologic Cross Section A-A'

Borrow Areas 3 and 4



- Boring Number
- Boring Location
- Water Level in Perched Water-Bearing Zone
- Perching Layer
- Water Level in Shallow Regional Aquifer




AR 052198

49785216

07/10/22/01 1:200 chertile-B.plt

Hydrogeologic Cross Section B-B'

Borrow Area 3




Note: Contacts between soil units are based upon interpolation between borings and represent our interpretation of subsurface conditions based on currently available data.

HARTCROWSER
J-4978-52 9/01
Figure 5

AR 052199

Hydrogeologic Cross Section C-C' Borrow Area 4



A4-B3-94 (185' N)

Exploration Number
Offset Distance and Direction

Exploration Location

Groundwater Level


Screened Interval

Horizontal Scale in Feet
0 200 400

Vertical Scale in Feet
0 40 80
Vertical Exaggeration x 5

HARTCROWSER
J-4978-52 10/01
Figure 8

Groundwater Elevation Contour Map - Shallow Regional Aquifer Borrow Area 3




Notes:
 1) Base map prepared from drawing provided by HMTB entitled "X_Loop.dwg", dated April 4, 2001.
 2) Wetland delineation prepared from drawing provided by Parametrix entitled, "W_0222001.dwg", dated February 20, 2001.
 3) Refer to Figures 4 and 5 for cross sections.
 4) Water levels based on highest observed readings.

Excavation Location and Number

- A3-B10-01 Boring with Observation Well (Hart Crowser)
- A3-B11-01 Boring (Hart Crowser)
- A3-B12-01 Boring with Observation Well (AGI)
- A3-B13-01 Boring (AGI)
- A3-B14-01 Test Pit (Hart Crowser)

- AA-AA Cross Section Location and Designation
- Measured Shallow Regional Aquifer Groundwater Elevation in Feet
- Shallow Regional Aquifer Water Level Elevation Contour in Feet (June 1998)

Groundwater Elevation Contour Map - Perched Water-Bearing Zone Borrow Areas 3 and 4



Notes:
 1) Base map prepared from drawing provided by HRTB entitled "X_topo.dwg", dated April 4, 2001.
 2) Wetland delineation prepared from drawing provided by Parametric entitled, "w_022001.dwg", dated February 20, 2001.
 3) Refer to Figures 4 through 6 for cross sections.
 4) Water levels based on highest observed readings.



- | | | |
|--------------------------------------|---|--|
| Exalation_Location_and_Number | AA-A' | Cross Section Location and Designation |
| ● AS-91-00 | Boring with Observation Well (Hart Crowser) | Perched Water-Bearing Zone Groundwater Elevation |
| ● AS-91-01 | Boring (Hart Crowser) | Perched Water-Bearing Zone Groundwater Elevation |
| ● AS-91-04 | Boring with Observation Well (AG) | Perched Water-Bearing Zone Groundwater Elevation |
| ○ AS-91-03 | Boring (AG) | Perched Water-Bearing Zone Groundwater Elevation |
| ■ A4-TP1-01 | Test Pit (Hart Crowser) | Perched Water-Bearing Zone Groundwater Elevation |

APPENDIX A
FIELD EXPLORATIONS METHODS AND ANALYSIS

Hart Crowser
4978-52 October 22, 2001

AR 052204

APPENDIX A FIELD EXPLORATIONS METHODS AND ANALYSIS

This appendix documents the processes Hart Crowser uses in determining the nature of the soils underlying the project site addressed by this report. The discussion includes information on the following subjects:

- Explorations and Their Location;
- The Use of Dual-Wall Percussion Hammer Drilling with Reverse Circulation;
- The Use of Auger Borings;
- Penetration Test Procedures;
- Groundwater Observation Well Installation;
- Excavation of Test Pits; and
- Hand-Auger Borings.

Explorations and Their Location

Subsurface explorations by Hart Crowser for Borrow Areas 3 and 4 consisted of thirteen dual-wall percussion hammer (DWPH borings) which were completed as monitoring wells; ten hollow-stem auger borings, five of which were completed as monitoring wells; and three test pits. The borings were designated A3-B8-98 through A3-B12-98; A3-B13-99 through A3-B17-99; A3-B18-01 through A3-B22-01; A4-B4-98 through A4-B6-98; and A4-B7-01 through A4-B11-01. Test pits were designated A4-TP1-01 through A4-TP3-01. Borings and test pits are designated using a system developed by others for the Third Runway Project Borrow Area Investigations, where 'A3' represents Borrow Area 3, 'B8' represents boring number 8, 'TP1' represents test pit 1, and '98' indicates the year the boring or test pit was completed. Logs for these explorations are presented on Figures A-2 to A-25 at the end of this appendix.

Subsurface explorations by Hart Crowser for the Haul Route consisted of three hand-auger borings. The explorations were designated HR-TP1-01 and HR-TP2-01, HR-B1-01 through HR-B3-01. Logs for these explorations are presented on Figures A-26 and A-27.

Subsurface explorations conducted in 1994 by AGI for Borrow Areas 3 and 4 consisted of ten hollow-stem auger borings, four of which were completed as monitoring wells. The borings were designated A3-B1-94 through A3-B7-94 (Borrow Area 3) and A4-B1-94 through A4-B3-94 (Borrow Area 4); logs are presented as Attachment A-1 to this appendix.

The boring logs within this appendix are the basis of Hart Crowser's interpretation of the drilling, sampling, and testing data. The logs indicate the

depth where the characteristics of soils and glacial sedimentary deposits change as follows:

- A hard line is used to show the contact between two geologically distinct units;
- A dashed line is used to show the contact between two dissimilar soils within a specific geologic unit; and
- The words "grades to" are used to mark the location of a gradual change in soil gradation or grain size distribution with increasing depth. Note that the new gradation indicated in this way persists over a distinct interval. Characteristics identified by "grades to" are intended to apply to the remainder of the unit below the notation on the log, or until a different change in gradation is indicated.

In the field, we classified the samples taken from the explorations according to the methods presented on Figure A-1 - Key to Exploration Logs. Attachment A-1 presents AGI's Soil Classification/Legend. These figures provide an explanation of the symbols and abbreviations used in the logs. The remainder of this appendix discusses exploration techniques utilized by Hart Crowser. Additional information on the techniques used by AGI is presented in AGI Technologies (1995).

Location of Explorations. Figures 2 and 3, which follow the main text, show the location of explorations. This report shows the actual locations and ground surface elevations, presented on the exploration logs, as they were established during site surveys by the Port of Seattle, dated May 28, 1998, and May 1999. 2001 explorations at Borrow Areas 3 and 4 were surveyed in June 2001. Explorations along the Haul Route were not surveyed; locations and elevations are based on hand taping from site features and topographic maps.

The Use of Dual-Wall Percussion Hammer Drilling with Reverse Circulation

With depths ranging from 22.0 to 141.2 feet below the ground surface, thirteen dual-wall percussion hammer borings, designated A3-B8-98 through A3-B12-98 and A4-B4-98 through A4-B6-98 were drilled from May 11 to 18, 1998. Explorations A3-B13-99 through A3-B17-99 were drilled later on April 15 to 23, 1999.

These eighteen borings incorporated a 9-inch outside diameter (6-inch inside diameter) dual-wall drive pipe and were advanced with a Becker diesel, pile-

driving hammer on a truck-mounted drill rig (AP1000). Layne Christensen Company was subcontracted by Hart Crowser to perform the drilling.

Dual-wall percussion hammer drilling with reverse circulation consists of a dual-walled pipe driven with a diesel drive hammer, while air is forced down the annulus of the double-wall drive pipe to the bit. The air returns up the inside pipe, carrying with it a continuous flow of drill cuttings that are discharged to an air cyclone. The air cyclone slows down the velocity of the air and drill-cutting mixture, separates the air from the cuttings, and allows for sample collection from the base of the cyclone.

The driving/drilling and sampling were continuously observed by an engineering geologist from Hart Crowser. Detailed field logs were prepared of each boring and each sample was visually and texturally classified in the field. Samples were collected from the air cyclone at 2-1/2- to 5-foot-depth intervals and placed into plastic bags tied with wire. Samples were collected to fill the plastic bags and represent the 2-1/2- to 5-foot sample collection interval; however, for clarity, cyclone samples are represented as 1-foot-thick samples on the logs. After soil sample collection, they were taken to Hart Crowser's laboratory for further testing.

The Use of Auger Borings

With depths ranging from 15.5 to 84.3 feet below the ground surface, ten hollow-stem auger borings, designated A3-B18-01 through A3-B22-01 and A4-B7-01 through A4-B11-01, were drilled from June 11 to 18, 2001. The borings used a 3-3/8-inch inside diameter hollow-stem auger and were advanced with a truck-mounted drill rig subcontracted by Hart Crowser. The drilling was continuously observed by an engineering geologist from Hart Crowser. Detailed field logs were prepared of each boring. Using the Standard Penetration Test (SPT), we obtained samples at 5-foot-depth intervals.

Penetration Test Procedures

This test is an approximate measure of soil and sediment density and consistency. To be useful, the results must be used with engineering judgment in conjunction with other tests. Penetration tests similar to the Standard Penetration Test (SPT; as described in ASTM D 1586) were performed to obtain disturbed samples. The tests employed a 3-inch outside diameter split-spoon sampler. Using a 140-pound hammer, free-falling about 30 inches (down-hole techniques were used), the sampler is driven into the material for 18 inches. The number of blows required to drive the sampler the last 12 inches only is the penetration resistance. This resistance, or blow count, measures the relative

density of granular soils and the consistency of cohesive material. The blow counts are plotted on the boring logs at their respective sample depths.

Samples are recovered from the split-spoon sampler, field classified, and placed into water tight jars. They are then taken to Hart Crowser's laboratory for further testing.

In the Event of Hard Driving

Occasionally very dense materials preclude driving the total 18-inch sample. When this happens, the penetration resistance is entered on logs as follows:

Penetration less than six inches. The log indicates the total number of blows over the number of inches of penetration.

Penetration greater than six inches. The blow count noted on the log is the sum of the total number of blows completed after the first 6 inches of penetration. This sum is expressed over the number of inches driven that exceed the first 6 inches. The number of blows needed to drive the first 6 inches are not reported. For example, a blow count series of 12 blows for 6 inches, 30 blows for 6 inches, and 50 (the maximum number of blows counted within a 6-inch increment for SPT) for 3 inches would be recorded as 80/9.

Groundwater Observation Well Installation

Observation wells were installed in eighteen of the Hart Crowser borings and four of the AGI borings. The Hart Crowser wells were constructed with flush-threaded 2-inch-diameter PVC and 10-foot-long screens (0.020-inch slot size). The following procedure was used to install the wells:

- Following completion of each boring to the target depth, the bottom of each boring was backfilled to the bottom-of-screen depth with cuttings and bentonite chips (as-needed).
- A 2-inch inside diameter, flush-threaded, Schedule 40 PVC screen (0.020-inch slots) and riser pipes were lowered through the dual-wall drive pipe.
- As the drive pipe was pulled out, silica sand (No. 10-20) was placed around and approximately 5 feet above the screened section. The depth to the top of the sand pack was recorded by sounding inside the annular space with a weighted measuring tape.

- The annular space of the well was sealed between the top of the sand pack to the bottom of the surface monument by placing bentonite chips in the hole.
- A concrete surface seal was then placed above the bentonite seal at ground surface, and a stickup-mounted monument set in concrete was placed over the finished groundwater observation well.

As-built construction details for observation wells are shown schematically on the respective logs.

Excavation of Test Pits

Five test pits, designated HR-TP1-01, HR-TP2-01, and A4-TP1-01 through A4-TP3-01 were excavated across the site with a tractor-mounted backhoe subcontracted by our firm. The sides of these excavated pits offer direct observation of the subgrade soils. The test pits were located by and excavated under the direction of an engineering geologist from Hart Crowser. The geologist observed the soil exposed in the test pits and reported the findings on a field log. He noted groundwater levels or seepage during excavation. The density/consistency of the soils (as presented parenthetically on the test pit logs to indicate their having been estimated) is based on visual observation only as disturbed soils cannot be measured for in-place density in the laboratory.

The test pit logs are presented on Figures A-25 and A-26.

Hand-Auger Borings

Three borings, designated HR-B1-01 through HR-B1-03, were drilled by a Hart Crowser geologist along the Haul Route using a hand-auger. These borings were drilled to conduct falling head infiltrometer tests. The geologist observed the soil cuttings from the borings and reported the findings on a field log. The density/consistency of the soils (as presented parenthetically on the boring logs to indicate their having been estimated) is based on visual observation only as disturbed soils cannot be measured for in-place density in the laboratory. The boring logs for these hand-auger borings are presented on Figure A-27.

F:\docs\jobs\497852\BA3&4DataReport.doc

Key to Exploration Logs

Sample Description

Classification of soils in this report is based on visual field and laboratory observations which include density/consistency, moisture condition, grain size, and plasticity estimates and should not be construed to imply field nor laboratory testing unless presented herein. Visual-manual classification methods of ASTM D 2488 were used as an identification guide.

Soil descriptions consist of the following:

Density/consistency, moisture, color, minor constituents, MAJOR CONSTITUENT, additional remarks.

Density/Consistency

Soil density/consistency in borings is related primarily to the Standard Penetration Resistance. Soil density/consistency in test pits is estimated based on visual observation and is presented parenthetically on the test pit logs.

SAND or GRAVEL	Standard Penetration Resistance (N) in Blows/Foot	SILT or CLAY	Standard Penetration Resistance (N) in Blows/Foot	Approximate Shear Strength in TS ²
Density		Consistency		
Very loose	0 - 4	Very soft	0 - 2	<0.125
Loose	4 - 10	Soft	2 - 4	0.125 - 0.25
Medium dense	10 - 30	Medium stiff	4 - 8	0.25 - 0.5
Dense	30 - 50	Stiff	8 - 15	0.5 - 1.0
Very dense	>50	Very stiff	15 - 30	1.0 - 2.0
		Hard	>30	>2.0

Moisture

Dry	Little perceptible moisture
Damp	Some perceptible moisture, probably below optimum
Moist	Probably near optimum moisture content
Wet	Much perceptible moisture, probably above optimum

Minor Constituents





Estimated Percentage

Not identified in description	0 - 5
Slightly (clayey, silty, etc.)	5 - 12
Clayey, silty, sandy, gravelly	12 - 30
Very (clayey, silty, etc.)	30 - 50




Legends

Sampling Test Symbols


BORING SAMPLES

-  Split Spoon
-  Shelby Tube
-  Cuttings
-  Core Run
- * No Sample Recovery
- P Tube Pushed, Not Driven


TEST PIT SAMPLES

-  Grab (Jar)
-  Bag
-  Shelby Tube

Test Symbols

- GS Grain Size Classification
- CN Consolidation
- UU Unconsolidated Un drained Triaxial
- CU Consolidated Undrained Triaxial
- CD Consolidated Drained Triaxial
- QU Unconfined Compression
- DS Direct Shear
- K_v Permeability
- PP Pocket Penetrometer
Approximate Compressive Strength in TSF
- TV Torvane
Approximate Shear Strength in TSF
- CBR California Bearing Ratio
- MD Moisture Density Relationship
- AL Atterberg Limits
 -  Water Content in Percent
 - Liquid Limit
 - Natural
 - Plastic Limit
- PID Photoionization Detector Reading
- CA Chemical Analysis
- DT In Situ Density Test

Groundwater Observations



I=1 A-1 STANDARD



HARTCROWSER

4978-52 9/01


Figure A-1

AR 052210

Boring Log A3-B8-98

Soil Descriptions


Ground Surface Elevation in Feet: 280.5



Depth in Feet:




Sample



PENETRATION RESISTANCE⁴

▲ Blows per Foot

1 2 5 10 20 50 100



● Water Content in Percent:

LAB TESTS (% Fines)



4978 A3B08.dwg net 8/30/01

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.



HARTCROWSER

J-4978

5/98

Figure A-2

AR 052211


Boring Log A3-B9-98

Soil Descriptions

Ground Surface Elevation in Feet: 270.0

<p>(Medium dense), slightly gravelly SAND over damp to wet, light brown, slightly silty, fine SAND with trace gravel. (Recessional; Type 3)</p> <p>Grades to gravelly</p>	<p>0</p> <p>5</p> <p>10</p> <p>15</p> <p>20</p> <p>25</p> <p>30</p> <p>35</p> <p>40</p> <p>45</p> <p>50</p> <p>55</p> <p>60</p> <p>65</p> <p>70</p> <p>75</p> <p>80</p> <p>85</p>	<p>ATD</p> <p>5/15/98</p>	<p>S-1A</p> <p>S-1B</p> <p>S-2</p> <p>S-3</p> <p>S-4</p> <p>S-5</p> <p>S-6</p> <p>S-7</p> <p>S-8</p> <p>S-9</p> <p>S-10A</p> <p>S-10B</p> <p>S-11</p> <p>S-12</p> <p>S-13</p>	<p>▲ Blows per Foot:</p> <p>1 2 5 10 20 50 100</p> <p>64/5</p> <p>56/3</p>	<p>LAB TESTS (% Fines)</p> <p>GS (8.1)</p> <p>GS₂₀₀ (5.0)</p> <p>GS (61.3)</p> <p>GS (23.8)</p>
<p>(Very stiff), moist to wet, light brown, slightly gravelly, sandy SILT (Weathered Till; Type 5)</p> <p>Grades to gravelly, very silty SAND to very sandy SILT. (Till; Type 5)</p>					
<p>Grades to silty, very gravelly SAND. (Type 4)</p>					
<p>Grades to silty, sandy GRAVEL. (Type 4)</p>					
<p>(Dense to very dense), moist to wet, light brown, silty, sandy GRAVEL. (Advance; Type 4)</p>					
<p>Wet, gray, slightly silty to silty, fine SAND. (Type 4)</p>					
<p>Grades to slightly silty, very gravelly SAND to very sandy GRAVEL (Type 2)</p>					
<p>Grades to slightly silty, sandy, fine to coarse GRAVEL (Type 2)</p>					
<p>Bottom of Boring at 60.0 Feet. Completed 5/12/98.</p>					

PENETRATION RESISTANCE⁴



● Water Content in Percent:

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.



J-4978 5/98
Figure A-3


AR 052212

4978 A309.dwg hsl B/30/01

Boring Log A3-B10-98

Soil Descriptions

Ground Surface Elevation in Feet: 318.6



1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.

HARTCROWSER
J-4978 5/98
Figure A-4 1/2

AR 052213

4978 A3-B10.dwg Rev. 8/30/01

Boring Log A3-B10-98

Soil Descriptions

(Very dense), wet, brown, slightly silty to silty, sandy GRAVEL. (Type 2 to Type 4)

Bottom of Boring at 96.0 Feet.
Completed 5/12/98.

Depth
in Feet


Sample

PENETRATION RESISTANCE⁴

LAB
TESTS

▲ Blows per Foot:

1 2 5 10 20 50 100



4978 A3B10x.dwg hcl

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.




J-4978 5/98
Figure A-4 2/2

AR 052214

Boring Log A3-B11-98

Soil Descriptions

Ground Surface Elevation in Feet: 348.4



4978 A3B11.dwg.hpl

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.

HARTCROWSER
J-4978 5/98
Figure A-5 1/2

AR 052215

Boring Log A3-B11-98

Soil Descriptions

Wet, gray, silty SAND with clods of Silt and trace Gravel. (Till-like; Type 4)

Grades to slightly gravelly, silty SAND. (Till-like)

Layer of clean, medium to coarse SAND.
(Very dense), wet, brown, slightly silty to silty, sandy GRAVEL. (Advance; Type 2)


Grades to silty. (Type 4)

Grades to slightly silty, very sandy GRAVEL. (Type 2)

Grades to sandy. (Type 2)

Grades to silty at bottom.
Bottom of Boring at 141.2 Feet.
Completed 5/13/98.

Depth in Feet




Sample

- S-41A
- S-41B
- S-41C
- S-42
- S-43
- S-44
- S-45
- S-46A
- S-46B
- S-47
- S-48
- S-49
- S-50
- S-51
- S-52
- S-53
- S-54
- S-55
- S-56A
- S-56B
- S-57
- S-58
- S-59
- S-60
- S-61
- S-62
- S-63
- S-64
- S-65
- S-66
- S-67
- S-68
- S-69A
- S-69B



PENETRATION RESISTANCE⁴

▲ Blows per Foot



LAB TESTS

(% Fines)



● Water Content in Percent:

4978 A3B11.dwg hf

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.



HARTCROWSER

J-4978 5/98

Figure A-5 2/2

AR 052216

Boring Log A3-B12-98

Soil Descriptions

Ground Surface Elevation in Feet: 241.1

(Medium dense to very dense), damp, brown, silty, fine SAND with plant roots near surface. (Recessional; Type 4)
 Grades to slightly silty, slightly gravelly (Type 3)

Grades to gravelly

Grades to trace gravel and color changes to gray.

Grades to non-gravelly.

Grades to gravelly

Grades to very sandy, fine to coarse GRAVEL. (Type 1)

Grades slightly silty, gravelly SAND. (Type 3)

Grades to no Gravel

Bottom of Boring at 35.0 Feet.
 Completed 5/14/98.

Depth in Feet

0
5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85


Sample

S-1
S-2A
S-2B
S-3
S-4
S-5
S-6
S-7
S-8
S-9
S-10
S-11A
S-11B
S-12
S-13
S-14
S-15

PENETRATION RESISTANCE⁴

▲ Blows per Foot

1 2 5 10 20 50 100



● Water Content in Percent

LAB TESTS (% Fines)

GS (10.0)

50/3

GS (7.5)

GS (1.7)

4978 A3-B12.dwg net

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-note techniques.
5. Refer to text for soil types.

HARTCROWSER

J-4978 5/98


Figure A-6

AR 052217

Boring Log A3-B13-99

Soil Descriptions


Approx. Ground Surface Elevation in Feet: 284.9



Depth in Feet

STANDARD PENETRATION RESISTANCE

Blows per Foot



LAB TESTS



D:\IN 10/2/01 1-1 (rwt)\XXXX0000\default.spc
 497802/Boring A3-B13-99

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Ground water level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts may not be representative of density due to gravel.


HARTCROWSER
 J-4978-02 4/99
 Figure A-7

AR 052218

Boring Log A3-B14-99

Soil Descriptions


Ground Surface Elevation in Feet: 290.5



Depth in Feet

PENETRATION RESISTANCE

LAB TESTS



DTN 10/2/01 1-1 (ref)xxxx0000/Delout.pcp
 497807/Boring A3-B14-99.dwg

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Ground water level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts may not be representative of density due to gravel.
5. Blow count may not be representative due to heave.




HARTCROWSER
 J-4978-02 4/99
 Figure A-8

AR 052219


Boring Log A3-B15-99

Soil Descriptions

Ground Surface Elevation in Feet: 299.7



PENETRATION RESISTANCE



LAB TESTS



DIN 10/2/01 1=1 (re)XXXXXXXXXX/Default.ppt
 497802/Boring A3-B15-99.dwg

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Ground water level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts may not be representative due to gravel.


HARTCROWSER
 J-4978-02 4/99
 Figure A-9

AR 052220

Boring Log A3-B16-99

Soil Descriptions


Ground Surface Elevation in Feet: 344.0



Depth in Feet

PENETRATION RESISTANCE

LAB TESTS



1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Ground water level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.

HARTCROWSER
J-4978-02 4/99
Figure A-10

AR 052221


Boring Log A3-B17-99

Soil Descriptions

Ground Surface Elevation in Feet: 302.6

	Stiff, damp, brown, slightly sandy, slightly gravelly SILT with occasional roots.
	Stiff, moist, brown, slightly silty, gravelly SAND with abundant roots.
	Dense, moist to wet, brown SAND.
	Becomes wet.
	Becomes very dense.
	Bottom of Boring at 22 Feet. Completed 4/22/99.

Depth in Feet:



LAB TESTS

--

• Water Content in Percent

01/10/2/01 1=1 (ref)XXXXXXXXXX/default.pcp
 497902/Boring A3-B17-99.dwg

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Ground water level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.

HARTCROWSER
 J-4978-02 4/99
 Figure A-11

Boring Log A3-B18-01

Soil Descriptions


Approx. Ground Surface Elevation in Feet: 240.2

Loose to medium dense, moist, brown, slightly silty, fine to medium SAND with trace gravel.


Grades to wet.

Bottom of Boring at 19.5 Feet.
Completed 06/18/01.


Depth in Feet



STANDARD PENETRATION RESISTANCE



LAB TESTS



BORING LOG 487652B.GPJ HC_CORP.GDT 10/2/01

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.


HARTCROWSER
J-4978-52 06/01
Figure A-12

AR 052223

Boring Log A3-B19-01

Soil Descriptions


Approx. Ground Surface Elevation in Feet: 238.0



BORING LOG 4978528.GPJ HC_CORP_GDT 8/30/01

STANDARD PENETRATION RESISTANCE

LAB TESTS



1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.



HARTCROWSER

J-4978-52

06/01

Figure A-13

AR 052223.01

Boring Log A3-B20-01

Soil Descriptions

Approx. Ground Surface Elevation in Feet: 247.3


Loose to medium dense, moist, brown, slightly gravelly, slightly silty, fine to medium SAND.

Becomes gravelly.


Becomes non-gravelly.

Bottom of Boring at 25.5 Feet.
Completed 06/18/01.


Depth in Feet



STANDARD PENETRATION RESISTANCE



LAB TESTS



BORING LOG 487852B GPJ HC CORP GDT 10/2/01

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.

HARTCROWSER

J-4978-52 06/01

Figure A-14

AR 052223.02

Boring Log A3-B21-01

Soil Descriptions


Approx. Ground Surface Elevation in Feet: 245.2

Loose to medium dense, moist, gray-brown, slightly silty to silty, fine to medium SAND.

Becomes wet.

Bottom of Boring at 25.5 Feet.
Completed 06/15/01.

Depth
in Feet




▽
ATD

STANDARD PENETRATION RESISTANCE

Sample

▲ Blows per Foot

1 2 5 10 20 50 100



LAB
TESTS



BORING LOG 497852B GPJ, HC, CORP. GDT. 8/30/01

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.



HARTCROWSER


J-4978-52

06/01

Figure A-15

AR 052224

Monitoring Well Log A3-B22-01



1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.

HARTCROWSER
J-4978-52 06/01
Figure A-16

AR 052225

Boring Log A4-B4-98


Soil Descriptions

Ground Surface Elevation in Feet: 383.0

	0	
(Dense to very dense), moist, light brown, slightly silty to silty SAND to gravelly SAND. (Recessional; Type 3)	-5	
(Very dense), moist, tan, slightly silty, very sandy GRAVEL to very gravelly SAND. (Advance; Type 2)	-10	
Grades to slightly silty, non-gravelly to gravelly, fine to medium SAND. (Type 3)	-15	
SAND becoming slightly finer and grades to trace gravel.	-20	
Sand becomes slightly coarser	-25	
Sand becomes slightly finer and grades to slightly gravelly.	-30	
Grades to gravelly.	-35	
Grades to trace gravel.	-40	
Grades to slightly gravelly.	-45	
Silt content decreases.	-50	
Grades very gravelly (Type 2)	-55	
Grades to wet, brown, clean to slightly silty, sandy GRAVEL. (Type 1)	-60	
Grades to very sandy GRAVEL	-65	
Grades gravelly to very gravelly, fine to medium SAND. (Type 1)	-70	
Grades to gravelly, fine SAND.	-75	
Grades to very gravelly, fine to coarse SAND.	-80	
Grades to gravelly, fine to medium SAND.	-85	


Depth in Feet

Sample



PENETRATION RESISTANCE⁴

▲ Blows per Foot
1 2 5 10 20 50 100



LAB TESTS (% Fines)



● Water Content in Percent

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.



HARTCROWSER


J-4978

5/98

Figure A-17

1/2

Boring Log A4-B4-98



4978 A4B04.dwg hcl

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.



HARTCROWSER

J-4978

5/98

Figure A-17

2/2


AR 052227

Boring Log A4-B5-98

Soil Descriptions

Ground Surface Elevation in Feet: 368.3

	(Medium dense), moist to wet, brown, gravelly, silty SAND. (Type 4)
	(Hard), moist to wet, tan to brown mottled, slightly gravelly, sandy SILT. (Weathered Till; Type 5)
	Grades to non-gravelly, non-sandy.
	Color changes to gray.
	Color changes to brown.
	Color changes to gray.
	Note: Silt is typically non-plastic with occasional thin layers of plastic silt or clay.
	(Very dense), damp, light brown, slightly silty, gravelly, fine SAND. (Advance; Type 3)
	Grades to slightly gravelly.
	Grades to very gravelly to gravelly, fine to medium SAND. (Type 1 to Type 2)
	Grades to very gravelly, fine to coarse SAND to very sandy, fine GRAVEL.
	Grades to gravelly, fine to medium SAND.
	Grades to slightly gravelly.
	Grades to gravelly.
	Grades to slightly gravelly.
	Grades to very gravelly.
	Grades to very sandy GRAVEL.
	(Very dense), damp to moist, gray, silty, gravelly SAND. (Till; Type 4)
	Bottom of Boring at 81.0 Feet. Completed 5/15/98.



1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.



J-4978 5/98

Figure A-18


AR 052228

4978 A4905.dwg hf

Boring Log A4-B6-98


Soil Descriptions

Ground Surface Elevation in Feet: 398.5




Depth in Feet

Sample




PENETRATION RESISTANCE⁴

▲ Blows per Foot



LAB TESTS (% Fines)



4978 A4006.dwg hcf

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-hole techniques.
5. Refer to text for soil types.



HARTCROWSER

J-4978


5/98

Figure A-19

1/2

AR 052229

Boring Log A4-B6-98



4978 A4B061.dwg hf

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be made.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.
4. Blow counts are for 140 pound hammer and 3-inch-diameter split-spoon sampler (i.e., Not conforming to ASTM D 1586) using down-blow techniques.
5. Refer to text for soil types.


HARTCROWSER
J-4978 **5/98**
Figure A-10 **2/2**

AR 052230

Monitoring Well Log A4-B7-01

Soil Descriptions


Approx. Ground Surface Elevation in Feet: 304.4




BORING LOG 497852M GPJ HC CORP GDT #20001

Top of Casing in Feet: 306.83
Casing stickup in Feet: 2.43

STANDARD PENETRATION RESISTANCE



LAB TESTS



1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.



HARTCROWSER


J-4978-52

06/01

Figure A-20

AR 052231

Monitoring Well Log A4-B8-01



BORING LOG 487852M.GPJ HC CORP GDT 10/2/01

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.

HARTCROWSER
J-4978-52 06/01
Figure A-21

AR 052232

Boring Log A4-B9-01


Soil Descriptions

Approx. Ground Surface Elevation in Feet: 304.8

Medium dense to very dense, moist to wet, brown-gray, non-gravelly to slightly gravelly, silty, fine SAND.

Bottom of Boring at 19.0 Feet.
Completed 06/15/01.


Depth
in Feet



BORING LOG 497852M.GPJ HC_CORP.GDT 8/30/01

STANDARD PENETRATION RESISTANCE

LAB TESTS



1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.



HARTCROWSER

J-4978-52

06/01


Figure A-22

AR 052233


Monitoring Well Log A4-B10-01

Soil Descriptions

Approx. Ground Surface Elevation in Feet: 295.4



Depth
in Feet



STANDARD PENETRATION RESISTANCE


Sample

▲ Blows per Foot

1 2 5 10 20 50 100



S-1
S-2
S-3
S-4
S-5
S-6
S-7



LAB TESTS



BORING LOG #87652M.GPJ HC CORP.GDT 10/201

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.



HARTCROWSER

J-4978-52

06/01

Figure A-23

AR 052234


Monitoring Well Log A4-B11-01

Soil Descriptions

Approx. Ground Surface Elevation in Feet: 295.5

0 - 5	Medium dense, wet, brown, gravelly, coarse SAND.
5 - 15	Stiff to hard, damp, brown to gray, slightly sandy, slightly gravelly to gravelly SILT.
15 - 20	Medium dense, wet, brown, gravelly, medium to coarse SAND.
20 - 35	Very stiff to hard, damp, blue-gray, very silty CLAY to very clayey SILT.
35 - 50	Dense to very dense, dry to moist, brown, non-gravelly to very gravelly SAND.
50 - 60	Hard, moist to wet, brown, gravelly SILT.
60 - 65	Dense to very dense, moist to wet, gray, slightly silty, fine SAND.
65 - 70	Grades to coarse SAND and sandy GRAVEL.
70 - 75	Bottom of Boring at 74.0 Feet. Completed 06/13/01.
75 - 80	Top of Casing in Feet: 297.13 Casing stickup in Feet: 1.63

Depth in Feet




Sample


S-1
S-2
S-3
S-4
S-5
S-6
S-7
S-8
S-9
S-10
S-11
S-12
S-13
S-14
S-15

STANDARD PENETRATION RESISTANCE

▲ Blows per Foot



LAB TESTS



BORING LOG 487852M GPJ HC CORP GDT 10/2/01

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater level, if indicated, is at time of drilling (ATD) or for date specified. Level may vary with time.



HARTCROWSER


J-4978-52

06/01


Figure A-24

AR 052235


Test Pit Log A4-TP1-01



Test Pit Log A4-TP2-01




Test Pit Log A4-TP3-01




3 LOGS PER PAGE 497852T GPJ HC_CORP GDT 8/30/01

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater conditions, if indicated, are at time of excavation. Conditions may vary with time.



HARTCROWSER
 J-4978-52 06/01
 Figure A-25

AR 052236

Test Pit Log HR-TP1-01



Test Pit Log HR-TP2-01



2 LOGS PER PAGE 497852TP GPJ HC_CORP GDT 10/2/01

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater conditions, if indicated, are at time of excavation. Conditions may vary with time.




J-4978-52 07/01


Figure A-26

AR 052237


Hand-Auger Boring Log HR-B1-01



Hand-Auger Boring Log HR-B2-01



Hand-Auger Boring Log HR-B3-01



3 LOGS PER PAGE 497852.GPJ MC_CORP.GDT 10/2/01

1. Refer to Figure A-1 for explanation of descriptions and symbols.
2. Soil descriptions and stratum lines are interpretive and actual changes may be gradual.
3. Groundwater conditions, if indicated, are at time of excavation. Conditions may vary with time.

HARTCROWSER

J-4978-52

07/01

Figure A-27

AR 052238

**ATTACHMENT A-1
AGI FIGURES**

UNIFIED SOIL CLASSIFICATIONS SYSTEM					
MAJOR DIVISIONS			TYPICAL NAMES		
COARSE GRAINED SOILS More than half is larger than No. 200 Sieve	GRAVELS More than half coarse fraction is larger than No. 4 sieve size	Clean gravels with little or no fines	GW		Well graded gravels, gravel-sand mixtures
			GP		Poorly graded gravels, gravel-sand mixtures
		Gravels with over 12% fines	GM		Silty Gravels, poorly graded gravel-sand-silt mixtures
			GC		Clayey gravels, poorly graded gravel-sand-clay mixtures
	SANDS More than half coarse fraction is larger than No. 4 sieve size	Clean sands with little or no fines	SW		Well graded sands, gravelly sands
			SP		Poorly graded sands, gravelly sands
		Sands with over 12% fines	SM		Silty sand, poorly graded sand-silt mixtures
			SC		Clayey sands, poorly graded sand-clay mixtures
FINE GRAINED SOILS More than half is smaller than No. 200 Sieve	SILTS AND CLAYS Liquid limit less than 50	ML		Inorganic silts and very fine sands, rock flour, silty or clayey fine sands, or clayey silts with slight plasticity	
		CL		Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays	
		OL		Organic clays and organic silty clays of low plasticity	
	SILTS AND CLAYS Liquid limit greater than 50	MH		Inorganic silts, micaceous or diatomaceous fine sandy or silty soils, elastic silts	
		CH		Inorganic clays of high plasticity, fat clays	
		OH		Organic clays of medium to high plasticity, organic silts	
HIGHLY ORGANIC SOILS			PT		Peat and other highly organic soils

SAMPLE <input type="checkbox"/> "Undisturbed" <input type="checkbox"/> Bulk/Grab <input type="checkbox"/> Not Recovered <input type="checkbox"/> Recovered, Not Retained	CONTACT BETWEEN UNITS Well Defined Change Gradational Change Obscure Change End of Exploration	PHYSICAL PROPERTY TESTS Consol - Consolidation LL - Liquid Limit PL - Plastic Limit Gs - Specific Gravity SA - Size Analysis TxS - Triaxial Shear TxP - Triaxial Permeability Perm - Permeability Po - Porosity MD - Moisture/Density DS - Direct Shear VS - Vane Shear Comp - Compaction UU - Unconsolidated, Undrained CU - Consolidated, Undrained CD - Consolidated, Drained
BLOWS PER FOOT Hammer is 140 pounds with 30-inch drop, unless otherwise noted S - SPT Sampler (2.0-Inch O.D.) T - Thin Wall Sampler (2.8-Inch Sample) H - Split Barrel Sampler (2.4-Inch Sample)		
MOISTURE DESCRIPTION Dry - Considerably less than optimum for compaction Moist - Near optimum moisture content Wet - Over optimum moisture content Saturated - Below water table, in capillary zone, or in perched groundwater		

AR 052240

P.O.S. Coordinates: E 12600 N 3200

Equipment Canterra CT-450


Land Surface Elevation 260 feet Date 12/17/93

laboratory
state

Moisture
content (%)

TV
density (pcf)

Blows per
Foot



BROWN SILTY SAND (SM) medium dense, moist; fine to medium grained (Recessional Outwash Unit 2).

GRAY SAND (SP) medium dense, moist; fine to medium grained, with a trace of gravel and silt (Recessional Outwash Unit 1).

GRAY SAND (SW) medium dense, moist; fine to coarse grained (Recessional Outwash Unit 1).

GRAY SILTY SAND (SM) medium dense, moist; fine grained (Recessional Outwash Unit 2).

Becomes very fine grained, with pockets of light brown silt.

MD 3.7 100 14

SA 6.4 97 16

MD 4.4 96 19

AGI
TECHNOLOGIES

Log of Area 3 Boring 1 (0-40') A3-B1-93
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE

A16a

JOB NUMBER
14.190.202

DRAWN
KM/SES

APPROVED

DATE
18 January 94

REVISED
OFF

DATE
27 Mar 95

LA3B1-2.PMS

AR 052241

P.O.S. Coordinates: E 12600 N 3200

Equipment Canterra CT-450

Land Surface Elevation 260 feet Date 12/17/93

Laboratory Tests

Moisture Content (%)

Dry Density (pcf)

Blows per Foot

Depth

Sample

40
16
45
24
50
55
60
65
70
75
80

GRAY SAND (SP) medium dense, wet to saturated; fine grained (Recessional Outwash Unit 1).

Groundwater encountered at 43 feet during drilling.

AGI
TECHNOLOGIES

Log of Area 3 Boring 1 (40-49') A3-B1-93
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE

A16b

JOB NUMBER
14.190.208

DRAWN
KM/SES

APPROVED

DATE
18 January 94

REVISED
DFF

DATE
27 Mar 95

AR 052242


P.O.S. Coordinates: E 12420 N 5780

Equipment Canterra CT-450

Land Surface Elevation 327 feet Date 12/17/93

Laboratory Tests
Moisture Content (%)
Dry Density (pcf)
Blows per Foot

Depth
Sample



AGI
TECHNOLOGIES

Log of Area 3 Boring 2 (0-40') A3-B2-93
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE

A17a

JOB NUMBER
14,190,208

DRAWN
KM/SES

APPROVED

DATE
18 January 94

REVISED
OFF

DATE
27 Mar 95


AR 052243

P.O.S. Coordinates: E 12420 N 5780 5180?

Equipment Canterra Ct-450

Land Surface Elevation 327 feet Date 12/17/93

Laboratory Tests	Moisture Content (%)	Dry Density (pcf)	Blows per Foot
SA	9.3	101	58



BROWN SILTY SAND (SM) very dense, saturated; very fine grained, with pockets of brown silt.

Groundwater encountered at 49 feet during drilling.

AGI
TECHNOLOGIES

Log of Area 3 Boring 2 (40-54') A 3-B2-93
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE

A17b

JOB NUMBER	DRAWN	APPROVED	DATE	REVISED	DATE
14.190.208	KMSES		18 January 94	DFF	27 Mar 95


LA381-2.PHE

AR 052244

P.O.S. Coordinates: N 2930 E 12.950

Equipment Mobile B-61

Land Surface Elevation 250 feet Date 12/2/94



Laboratory Tests	Moisture Content (%)	Dry Density (pcf)	Blows per Foot	Depth (feet)	Sample
MD	5.4	101	11	0	
MD, SA	6.8	94	9	5	
MD	3.7	95	15	10	
COMP				15	
MD, SA	15.6	112	14	20	
MD	11.6	96	18	25	
MD, SA	6.2	102	17	30	
MD	22.3	101	44	35	
MD	23.6	99	19	40	

BROWN SAND (SP) medium dense, moist; fine to medium grained, with a trace of gravel (Recessional Outwash - Unit 1).

Becomes loose.

Becomes gray and medium dense.

BROWN SILTY SAND (SM) medium dense, moist; gravelly silt interbeds (Recessional Outwash - Unit 2).

RED BROWN SAND (SP) medium dense, moist; fine grained (Recessional Outwash - Unit 1).

Becomes gray, dense, and fine to medium grained.

Becomes medium dense and saturated, with silt.

AGI

TECHNOLOGIES

Log of Area 3 Boring 3 (0-40') A3-83-94

HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE

A18a


H3mw.ccr
PROJECT NO. 14.190.208
DRAWN ECR
DATE 6 December 94
APPROVED
REVISED
DATE

P.O.S. Coordinates: N 2930 E 12.950


Equipment Mobile B-61

Land Surface Elevation 250 feet Date 12/2/94

Laboratory Tests
Moisture Content (%)
Dry Density (pcf)
Blows per Foot
Depth (feet)
Sample



SA
COMP



Groundwater encountered at 37.5 feet during drilling.
Boring converted into piezometer on 12/2/94.

AGI
TECHNOLOGIES

Log of Area 3 Boring 3 (40-49') A3-B3-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A18b

H3-40.cdr PROJECT NO. 14.190.208 DRAWN ECR DATE 6 December 94 APPROVED REVISED DATE

AR 052246

P.O.S. Coordinates: N 3480 E 12.710

Equipment Mobile B-61

Land Surface Elevation 243 feet Date 12/2/94

Laboratory Tests
Moisture Content (%)
Dry Density (pcf)
Blows per Foot

Depth (feet)
Sample

Laboratory Tests	Moisture Content (%)	Dry Density (pcf)	Blows per Foot
MD	2.5	104	21
MD	13.4	96	16
MD	4.6	99	24
MD,SA	2.9	132	29
COMP			
MD,SA	5.7	144	90
MD,SA	6.8	142	80
MD	4.4	132	81

0
BROWN SAND (SP) loose, wet; fine to medium grained, with organic material (Recessional Outwash - Unit 1).

5
GRAY BROWN SAND (SP) medium dense, moist; fine to coarse grained, with a trace of gravel (Recessional Outwash - Unit 1).

10

15
Becomes red brown.

20
GRAY SAND (SW) dense, moist; fine to coarse grained, with gravel and a trace of silt (Recessional Outwash - Unit 2).

25
Becomes very dense, wet; with fine to medium gravel.
GRAY GRAVEL (GW) very dense, saturated; fine to coarse grained, with sand and a trace of silt (Recessional Outwash - Unit 2).

30

35
Becomes brown.

40
Groundwater encountered at 25.5 feet during drilling. Boring backfilled with bentonite and cuttings on 12/2/94.

AGI TECHNOLOGIES	Log of Area 3 Boring 4 A3-B4-94				PLATE A19
	HNTB/Runway Borrow Source Study Sea Tac, Washington				
H3mw.cdr	PROJECT NO. 14,190,208	DRAWN ECR	DATE 6 December 94	APPROVED	REVISED


AR 052247

P.O.S. Coordinates: N 4450 E 12.920

Equipment Mobile B-61

Land Surface Elevation 252 feet Date 12/2/94

Laboratory Tests	Moisture Content (%)	Dry Density (pcf)	Blows per Foot
MD,SA	16.4	11115	
MD,LL PL	20.4	107	29
MD,SA COMP	17.4	104	33
MD,SA	7.6	134	50/4"



BROWN SILTY SAND (SM) medium dense, wet: fine to medium grained, with some organics (Recessional Outwash - Unit 2).

Becomes gray, with some gravel.

GRAY CLAY (CL) hard, moist: with sand and some fine gravel (Recessional Outwash - Unit 2).

BROWN SAND (SP) very dense, moist: fine to medium grained, with a trace of gravel (Advance Outwash - Unit 1).

RED BROWN SILTY SAND (SM) dense, wet: fine grained (Advance Outwash - Unit 2).

BROWN GRAVEL (GP) very dense, wet: fine to medium grained, with sand and a trace of silt (Advance Outwash - Unit 3).

Becomes gray.

Becomes saturated.

AGI
TECHNOLOGIES

Log of Area 3 Boring 5 (0-40') A3-B5-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A20a

H3mw.cdr	PROJECT NO. 14.190.208	DRAWN ECR	DATE 6 December 94	APPROVED	REVISION	DATE
----------	---------------------------	--------------	-----------------------	----------	----------	------

AR 052248

P.O.S. Coordinates: N 4450 E 12.920

Equipment Mobile B-61

Land Surface 252 feet Date 12/2/94
Elevation

Laboratory Tests
Moisture Content (%)
Dry Density (pcf)
Blows per Foot
Sample



MD 7.0 144 50/4"

50/4"

37

GRAY SILT (ML) hard, moist; with fine sand (Pre-Vashon Drift).

Groundwater encountered at 41 feet during drilling.

Boring backfilled with bentonite and cuttings on 12/2/94.

AGI
TECHNOLOGIES

Log of Area 3 Boring 5 (40-54') A3-B5-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A20b

H3-40.cdr PROJECT NO. 14.190.208 DRAWN ECR DATE 6 December 94 APPROVED REVISD DATE


AR 052249

P.O.S. Coordinates: N 4785 E 12,840

Equipment Mobile B-61

Land Surface Elevation 268 feet Date 12/3/94

Laboratory Tests
Moisture Content (%)
Dry Density (pcf)
Blows per Foot



BROWN SAND (SP) dense, moist; fine to medium grained, mottled, with gravel and silt (Recessional Outwash - Unit 1).

GRAY SILT (ML) hard, moist; mottled (Recessional Outwash - Unit 2).

GRAY GRAVEL (GP) very dense, moist; fine grained, with silt (Advance Outwash - Unit 3).

GRAY GRAVEL (GW-GM) very dense, wet; fine to coarse grained, with sand and silt (Advance Outwash - Unit 3).

MD 10.2 126 37

MD,SA 2.1 131 53

COMP

MD 9.8 132 87

MD,SA 13.7 110 50/5"

AGI
TECHNOLOGIES

Log of Area 3 Boring 6 (0-40') A3-B6-94
HNTB/Runway Borrow Source Study
Sea Tac, Washington

PLATE
A21a

H3mw.cdr

PROJECT NO.
14,190.208

DRAWN
ECR

DATE
6 December 94

APPROVED

REVISED

DATE

AR 052250

P.O.S. Coordinates: N 4785 E 12,840

Equipment Mobile B-61

Land Surface 268 feet Date 12/3/94
Elevation

Laboratory Tests
Moisture Content (%)
Dry Density (pcf)
Blows per Foot
Depth (feet)
Sample


MD,SA 8.2 136 50/5"

50/4"

50/6"

50/3"

50/3"



Becomes saturated

GRAY SAND (SP) very dense, saturated; with fine gravel (Advance Outwash - Unit 1).

Groundwater encountered at 51 feet during drilling.

Boring backfilled with bentonite and cuttings on 12/3/94.

AGI
TECHNOLOGIES

Log of Area 3 Boring 6 (40-63') A3-B6-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE

A21b

H3-40.cdr

PROJECT NO. 14,190.208

DRAWN ECR

DATE 6 December 94

APPROVED

REVISED


DATE

AR 052251

P.O.S. Coordinates: N 5590 E 12.900

Equipment Mobile B-61

Land Surface 315 feet Date 12/22/94
Elevation



Laboratory Tests	Moisture Content (%)	Dry Density (pcf)	Blows per Foot
MD, SA COMP	12.3	99	4
MD, SA	13.7	120	70
SA, COMP	8.6		50/6"
MD	5.8	129	50/5"
MD, SA	15.5	111	13
COMP			50/6"

Depth (feet) Sample

0

5

10

15

20

25

30

35

40

BROWN SAND (SP) loose, moist; fine to medium grained, with a trace of fine gravel and silt (Recessional Outwash - Unit 1).

BROWN SILTY SAND (SM) medium dense, moist; fine to coarse grained, with gravel (Recessional Outwash - Unit 2).

BROWN SAND (SM) very dense, wet; fine to coarse grained, with gravel (Advance Outwash - Unit 1).

BROWN SAND (SW-SM) very dense, wet; fine to coarse grained, with gravel and silt (Advance Outwash - Unit 1)

BROWN GRAVEL (GP) very dense, moist; fine to coarse grained gravel, medium grained sand (Advance Outwash - Unit 3).

BROWN SAND (SP) very dense, moist; fine to medium grained (Advance Outwash - Unit 1).

BROWN SAND (SW-SM) medium dense, saturated; fine to coarse grained, with fine gravel and silt (Advance Outwash - Unit 1).

BROWN SANDY SILT (ML) hard, saturated, fine grained (Advance Outwash - Unit 2).

V 278

AGI
TECHNOLOGIES

Log of Area 3 Boring 7 (0-40') A3-B7-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A22a

H3mw.cdr

PROJECT NO.
14,190,208

DRAWN
ECR

DATE
6 December 94

APPROVED

REVISED


DATE

AR 052252

P.O.S. Coordinates: N 5590 E 12.900

Equipment Mobile B-61

Land Surface 315 feet Date 12/22/94
Elevation



Laboratory Tests	Moisture Content (%)	Dry Density (pcf)	Blows per Foot	Depth (feet)	Sample
MD,SA	24.5	100	54	40	
				45	
				50/4"	
				50	
				50/5"	
				55	
MD,SA	6.8	130	50/6"	55	
				60	
				50/5"	
				65	
MD	5.7	116	50/3"	70	
				75	
				50/3"	
MD,SA	8.3	115	50/3"	80	

GRAY CLAY (CL) hard, moist: with some fine gravel (Advance Outwash - Unit 2).

BROWN GRAVEL (GP-GM) very dense, wet: fine to medium grained gravel, with sand and pockets of silt (Advance Outwash - Unit 3).

AGI
TECHNOLOGIES

Log of Area 3 Boring 7 (40-80') A3-B7-94
HNTB/Runway Borrow Source Study
Sea Tac, Washington

PLATE
A22b

H3-40.cdr

PROJECT NO.
14,190,208

DRAWN
ECR

DATE
6 December 94

APPROVED

REVISED

DATE


AR 052253

P.O.S. Coordinates: N 5590 E 12,900


Equipment Mobile B-61

Land Surface Elevation 315 feet Date 12/22/94

Laboratory Tests
Moisture Content (%)
Dry Density (pcf)
Blows per Foot



MD 20.4 103 50/2"



Becomes saturated.

DARK GRAY GRAVEL (GW) very dense, saturated; fine to coarse grained gravel, with some sand and silt (Advance Outwash - Unit 3).

Groundwater encountered at 82 feet during drilling.

Perched groundwater encountered at 33 feet during drilling.

Boring converted into piezometer on 12/22/94.

AGI
TECHNOLOGIES

Log of Area 3 Boring 7 (80-102.5') A3-B7-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A22c


H3-80.ccr PROJECT NO. 14,190,208 DRAWN ECR DATE 6 December 94 APPROVED REVISD DATE

AR 052254

P.O.S. Coordinates: N 6465 E 12,070

Equipment Mobile B-61

Land Surface Elevation 395 feet Date 12/21/94



Laboratory Tests	Moisture Content (%)	Dry Density (pcf)	Blows per Foot	Depth (feet)	Sample
				0	
MD, SA	20.5	85	9	5	
			67	10	
SA, COMP			50/6"	15	
SA	7.5		50/5"	20	
MD	7.1	11.5	67	25	
			50/5"	30	
MD, SA	6.3	106	50/6"	35	
			50/5"	40	

DARK BROWN SILT (ML) medium stiff, moist; with some sand and organics (Alluvium).

REDDISH BROWN SILTY SAND (SM) loose, moist; fine to coarse grained, with gravel (Alluvium).

GRAY SAND (SW-SM) very dense, moist; fine to coarse grained, with gravel and silt (Advance Outwash - Unit 1).

GRAY SAND (SP) very dense, moist; fine grained, with trace silt (Advance Outwash - Unit 1).

AGI
TECHNOLOGIES

Log of Area 4 Boring 1 (0-40') A4-B1-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A23a


H4mw.cdr PROJECT NO. 14,190.208 DRAWN ECR DATE 6 December 94 APPROVED _____ REVISED _____ DATE _____

AR 052255

P.O.S. Coordinates: N 6465 E 12,070

Equipment Mobile B-61

Land Surface Elevation 395 feet Date 12/21/94



GRAY SAND (SW) very dense, moist; fine to coarse grained, with silt and a trace of fine gravel (Advance Outwash - Unit 1).

GRAY SAND (SP) very dense, moist; fine grained (Advance Outwash - Unit 1).

GRAY SAND (SW) very dense, wet; fine to coarse grained, with fine gravel (Advance Outwash - Unit 1).

GRAY SAND (SP-SM) very dense, wet; fine to medium grained, with trace fine gravel and silt (Advance Outwash - Unit 1).

AGI
TECHNOLOGIES

Log of Area 4 Boring 1 (40-80') A4-B1-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A23b

PROJECT NO. 14.190.208 DRAWN ECR DATE 6 December 94 APPROVED _____ REVISED _____ DATE _____

H4-40.cdr

AR 052256

P.O.S. Coordinates: N 6465 E 12.070

Equipment Mobile B-61

Land Surface Elevation 395 feet Date 12/21/94


Laboratory Tests
Moisture Content (%)
Dry Density (pcf)
Blows per Foot

Depth (feet)
Sample



MD,SA 6.8 110 50/5"

MD 11.0 127 50/6"



GRAY SAND (SW) very dense, wet; fine to coarse grained, with gravel and a trace of silt (Advance Outwash - Unit 1).

GRAY SAND (SP) very dense, saturated, fine to medium grained, with silt interbeds (Advance Outwash - Unit 1).

BROWN GRAVEL (GP-GM) very dense, saturated: fine to coarse grained, with sand and silt (Advance Outwash - Unit 3).

BROWN SILTY SAND (SM) very dense, saturated: fine grained (Advance Outwash - Unit 2).

Color changes to dark gray.

Groundwater encountered at 98 feet during drilling. Boring converted into piezometer on 12/22/94.

AGI
TECHNOLOGIES

Log of Area 4 Boring 1 (80-118.3') A4-B1-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A23c

H4-30 car

PROJECT NO.
14.190.208

DRAWN
ECR

DATE
6 December 94

APPROVED

REVISED


DATE

AR 052257

P.O.S. Coordinates: N 6790 E 11.680

Equipment Mobile B-61

Land Surface Elevation 343 feet Date 12/5/94



AGI
TECHNOLOGIES

Log of Area 4 Boring 2 A4-B2-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A24

H4mw.cdr PROJECT NO. 14.190.208 DRAWN ECR DATE 6 December 94 APPROVED REVISOR DATE

AR 052258

P.O.S. Coordinates: N 6890 E 13.015

Equipment Mobile B-61

Land Surface 296 feet Date 12/5/94
Elevation

Laboratory Tests
Moisture Content (%)
Dry Density (pcf)
Blows per Foot

Depth (feet)
Sample

Laboratory Tests	Moisture Content (%)	Dry Density (pcf)	Blows per Foot	Depth (feet)
MD	15.7	94	10	0
				5
				40
MD,SA	9.4	134	96	10
				15
				50/6"
MD,PL LL	7.7	110	50/6"	20
				25
				50/4"
				30
				35
				40

DARK BROWN SANDY SILT (ML) medium dense, wet; with organic material (Weathered Till).

BROWN SILTY SAND (SM) medium dense, moist; fine to medium grained, mottled, with gravel and organic material (Weathered Till).

GRAY SILTY SAND (SM) dense, moist; fine to coarse grained, with gravel (Till - Unit 1).

Becomes very dense, wet.

GRAY CLAYEY SILT (ML) very hard, moist; laminated (Pre-Vashon Drift).

Groundwater not encountered during drilling.

Boring backfilled with bentonite and cuttings on 12/5/94.

AGI
TECHNOLOGIES

Log of Area 4 Boring 3 A4-B3-94
HNTB/Runway Borrow Source Study
SeaTac, Washington

PLATE
A25

H4mw.cdr

PROJECT NO.
14.190.208

DRAWN
ECR

DATE
6 December 94

APPROVED

REVISED

DATE

AR 052259

APPENDIX B
LABORATORY TESTING PROGRAM

APPENDIX B LABORATORY TESTING PROGRAM

Hart Crowser completed a laboratory testing program to evaluate the basic index and geotechnical engineering properties of the site soils. Disturbed bag samples from the drill rig cyclone and jar samples from penetration tests were selected for laboratory testing with the following items in mind:

- Suitability of soils for use as wet weather fill;
- Soils representative of the geologic unit;
- Consistency within a geologic unit; and
- Sampling soils generally within the depth of the proposed excavation (based on existing information).

The tests performed and the procedures followed are outlined below.

Soil Classification

Field Observation and Laboratory Analysis. Soil samples from the explorations were visually classified in the field and then taken to our laboratory where the classifications were verified in a relatively controlled laboratory environment. Field and laboratory observations include density/consistency, moisture condition, and grain size and plasticity estimates.

The classifications of selected samples were checked by laboratory tests such as grain size analyses and 200 wash. Classifications were made in general accordance with the Unified Soil Classification (USC) System, ASTM D 2487, as presented on Figure B-1.

Water Content Determinations

Water contents were determined for specific samples recovered in the explorations in general accordance with ASTM D 2216, as soon as possible following their arrival in our laboratory. Water contents were not determined for very small samples nor samples where large gravel contents would result in values considered unrepresentative. The results of these tests are plotted at the respective sample depth on the exploration logs. In addition, water contents are routinely determined for samples subjected to other testing. These are also presented on the exploration logs.

Water contents were compared for samples of cuttings from the drill cyclone bag samples with water contents obtained from conventional SPT split-spoon samples, as shown on the drill logs. In some, but not all, cases it appeared that the cuttings samples were slightly drier than the SPT samples, as might be expected. Superficially it appears that the more silty samples typically exhibited less drying due to drill action compared to coarser-grained samples. In general we recommend that moisture content of SPT samples be considered more representative of *in situ* conditions compared to those of cuttings samples.

Grain Size Analysis (GS)

Grain size distribution was analyzed on representative samples in general accordance with ASTM D 422. Wet sieve analysis was used to determine the size distribution greater than the U.S. No. 200 mesh sieve. The size distribution for particles smaller than the No. 200 mesh sieve was determined by the hydrometer method for a selected number of samples. The results of the tests are presented as curves on Figures B-2 through B-7 plotting percent finer by weight versus grain size.

200-Wash (GS₂₀₀)

Several samples were subjected to a modified grain size classification known as a 200-wash. The portion of individual samples passing the 3/4-inch sieve was "washed" through the No. 200 mesh sieve to determine the relative percentages of coarse- and fine-grained material in the samples. The tests were performed in general accordance with ASTM D 1140. The results are presented on the boring logs.

F:\docs\jobs\497852\BA3&4DataReport.doc

Unified Soil Classification (USC) System

Soil Grain Size

Size of Opening in Inches	Number of Mesh per inch (US Standard)	Grain Size in Millimetres
12	6	4
8	4	2
6	2	1 1/2
4	1	1
3/4	3/4	3/4
3/8	5/8	5/8
1/2	1/2	1/2
3/8	1/4	3/8
1/4	3/8	1/4
3/16	4	3/16
1/8	10	1/8
3/32	20	3/32
1/16	40	1/16
3/64	60	3/64
1/32	100	1/32
3/128	200	3/128
1/64	250	1/64
3/256	300	3/256

COBBLES		GRAVEL	SAND	SILT and CLAY
Coarse-Grained Soils			Fine-Grained Soils	

Coarse-Grained Soils

G W	G P	G M	G C	S W	S P	S M	S C
Clean GRAVEL <5% fines		GRAVEL with >12% fines		Clean SAND <5% fines		SAND with >12% fines	
GRAVEL >50% coarse fraction larger than No. 4				SAND >50% coarse fraction smaller than No. 4			
Coarse-Grained Soils >50% larger than No. 200 sieve							

$$G W \text{ and } S W \left(\frac{D_{60}}{D_{10}} \right) > 4 \text{ for } G W \text{ \& } 1 \leq \left(\frac{D_{30}}{D_{10} \times D_{60}} \right) \leq 3$$

G P and S P Clean GRAVEL or SAND not meeting requirements for G W and S W

G M and S M Atterberg limits below A line with PI < 4


G C and S C Atterberg limits above A Line with PI > 7

* Coarse-grained soils with percentage of fines between 5 and 12 are considered borderline cases required use of dual symbols.

D₁₀, D₃₀, and D₆₀ are the particles diameter of which 10, 30, and 60 percent, respectively, of the soil weight are finer.

Fine-Grained Soils

ML	CL	OL	MH	CH	OH	Pt
SILT		CLAY	Organic	SILT	CLAY	Organic
Soils with Liquid Limit <50%			Soils with Liquid Limit >50%			Highly Organic Soils
Fine-Grained Soils >50% smaller than No. 200 sieve						



HARTCROWSER


J-4978-02

8/99

Figure B-1

AR 052264

GRAIN SIZE DISTRIBUTION TEST REPORT



	% +75 mm	% GRAVEL	% SAND	% SILT	% CLAY
●	0.0	3.6	88.1	8.3	
▲	0.0	0.8	67.9	31.3	
■	0.0	41.7	42.1	16.2	

	LL	PI	D ₈₅	D ₆₀	D ₅₀	D ₃₀	D ₁₅	D ₁₀	C _c	C _u
●			0.44	0.30	0.26	0.188	0.1255	0.0909	1.31	3.2
▲			0.25	0.15	0.12					
■			23.17	5.50	1.17	0.254				


MATERIAL DESCRIPTION	USCS	NAT. MOIST.
● Slightly silty SAND	SP-SM	6%
▲ Very silty SAND	SM	6%
■ Silty, very gravelly SAND	SM	11%

Remarks:

Project: 3rd Runway
 ● Location: A3-B8-98, S-1, Depth 5 Feet
 ▲ Location: A3-B8-98, S-7, Depth 30 Feet
 ■ Location: A3-B8-98, S-13, Depth 60 Feet

AR 052265

GRAIN SIZE DISTRIBUTION TEST REPORT



	%+75mm	% GRAVEL	% SAND	% SILT	% CLAY
●	0.0	1.0	90.9	8.1	
▲	0.0	2.7	36.0	61.3	
■	0.0	39.8	40.0	20.2	

	LL	PI	D ₈₅	D ₆₀	D ₅₀	D ₃₀	D ₁₅	D ₁₀	C _c	C _u
●			0.52	0.33	0.28	0.203	0.1354	0.0981	1.29	3.3
▲			0.38							
■			19.72	4.62	0.83	0.221				


MATERIAL DESCRIPTION	USCS	NAT. MOIST.
● Slightly silty SAND	SP-SM	11%
▲ Very sandy SILT	ML	26%
■ Silty, very gravelly SAND	SM	8%

Remarks:

Project: 3rd Runway
 ● Location: A3-B9-98, S-1A, Depth 5 Feet
 ▲ Location: A3-B9-98, S-6, Depth 28 Feet
 ■ Location: A3-B9-98, S-8, Depth 35 Feet

AR 052266

GRAIN SIZE DISTRIBUTION TEST REPORT



	% > 75 mm	% GRAVEL	% SAND	% SILT	% CLAY
●	0.0	17.3	63.6	19.1	
▲	0.0	11.0	81.3	7.7	
■	0.0	62.4	21.0	16.6	

	LL	PI	D ₈₅	D ₅₀	D ₃₀	D ₁₅	D ₁₀	C _c	C _u
●			5.96	0.67	0.46	0.242			
▲			1.24	0.50	0.41	0.293	0.1936	0.1180	1.47
■			35.77	21.98	14.69	0.578			4.2


MATERIAL DESCRIPTION		USCS	NAT. MOIST.
● Gravelly, silty SAND		SM	11%
▲ Slightly silty, slightly gravelly SAND		SP-SM	11%
■ Silty, sandy GRAVEL		GM	6%

Remarks:

Project: 3rd Runway
 ● Location: A3-B10-98, S-2, Depth 10 Feet
 ▲ Location: A3-B10-98, S-5A, Depth 25 Feet
 ■ Location: A3-B10-98, S-13A, Depth 65

AR 052267

GRAIN SIZE DISTRIBUTION TEST REPORT



	%+75 _{mm}	% GRAVEL	% SAND	% SILT	% CLAY
●	0.0	1.2	74.2	24.6	
▲	0.0	14.3	78.1	7.6	
■	0.0	58.0	40.8	1.2	

	LL	PI	D ₈₅	D ₆₀	D ₅₀	D ₃₀	D ₁₅	D ₁₀	C _c	C _u
●			0.42	0.23	0.19	0.111				
▲			4.22	0.44	0.36	0.251	0.1603	0.1135	1.25	3.9
■			19.03	9.65	6.52	2.982	1.3630	0.7754	1.19	12.4


MATERIAL DESCRIPTION	USCS	NAT. MOIST.
● Silty SAND	SM	18%
▲ Slightly silty, gravelly SAND	SP-SM	16%
■ Very sandy GRAVEL	GW	10%

Remarks:

Project: 3rd Runway
 ● Location: A3-B11-98, S-46A, Depth 95 Feet
 ▲ Location: A3-B12-98, S-11A, Depth 25 Feet
 ■ Location: A3-B12-98, S-12, Depth 27 Feet

AR 052268

GRAIN SIZE DISTRIBUTION TEST REPORT




	% +75 mm	% GRAVEL	% SAND	% SILT	% CLAY
●	0.0	49.9	42.9	7.2	
▲	0.0	71.7	25.6	2.7	
■	0.0	20.1	76.7	3.2	

	LL	PI	D ₈₅	D ₆₀	D ₅₀	D ₃₀	D ₁₅	D ₁₀	C _c	C _u
●			21.83	8.49	4.72	0.667	0.2748	0.1816	0.29	46.8
▲			23.88	16.01	12.87	5.682	0.5553	0.3308	6.10	48.4
■			18.62	0.67	0.54	0.361	0.2585	0.2150	0.91	3.1

MATERIAL DESCRIPTION	USCS	NAT. MOIST.
● Slightly silty, very sandy GRAVEL	GP-GM	8%
▲ Sandy GRAVEL	GP	5%
■ Gravelly SAND	SP	2%

Remarks:	Project: 3rd Runway ● Location: A4-B4-98, S-7, Depth 13 Feet ▲ Location: A4-B4-98, S-33A, Depth 66 Feet ■ Location: A4-B5-98, S-21A, Depth 45 Feet
----------	---

GRAIN SIZE DISTRIBUTION TEST REPORT



	% +75 mm	% GRAVEL	% SAND	% SILT	% CLAY
●	0.0	66.2	29.4	4.4	
▲	0.0	62.3	33.3	4.4	

	LL	PI	D ₈₅	D ₆₀	D ₅₀	D ₃₀	D ₁₅	D ₁₀	C _c	C _u
●			24.13	13.72	10.63	2.380	0.3728	0.2521	1.64	54.5
▲			29.17	17.12	12.55	0.560	0.2205	0.1526	0.12	112.2

MATERIAL DESCRIPTION	USCS	NAT. MOIST.
● Sandy GRAVEL	GW	6%
▲ Very sandy GRAVEL	GP	4%

Remarks:	Project: 3rd Runway ● Location: A4-B6-98, S-12A, Depth 25 Feet ▲ Location: A4-B6-98, S-35, Depth 35 Feet
----------	--

**APPENDIX C
BORROW AREA 3 PERCHED WATER-BEARING ZONE
SLUG TEST ANALYSIS**

**APPENDIX C
BORROW AREA 3 PERCHED WATER-BEARING ZONE
SLUG TEST ANALYSIS**

This appendix documents the process Hart Crowser uses in conducting slug tests for purposes of evaluating the perched water-bearing zone in Borrow Area 3. The discussion addresses the Hydraulic Conductivity Testing (Slug Testing) conducted in four wells.

Hydraulic Conductivity Testing (Slug Testing)

Hydraulic conductivity testing was performed using the slug test method for explorations A3-13-99 through A3-17-99. In this method, the water level (hydraulic head) in the well is rapidly raised or lowered, and the rate at which it returns to its initial state is used to calculate hydraulic conductivity for the formation surrounding the well screen. Data were collected using an Aquistar data logger in conjunction with a Instrumentation Northwest PSI9000 pressure transducer. Tests were conducted as follows:

A transducer was set in the well and allowed to equilibrate with ambient conditions, and background water level data were collected.

One or two slug rods (solid PVC rods) were rapidly introduced into the well (causing a near-instantaneous rise in water level), to initiate a falling head test. Water level data were collected in logarithmically increasing time increments using the data logger and transducer. For wells where depth to water was small, a falling head test was not attempted.

Water level in the well was allowed to re-equilibrate.

The slug rod or rods were rapidly pulled from the well (causing a near-instantaneous drop in water level) to initiate a rising head test. Water level data were collected in logarithmically increasing time increments using the data logger and transducer.

Most of the wells responded reasonably quickly, and therefore multiple slug tests were performed for most wells.

Data were pre-processed as described in Butler (1998), and hydraulic conductivity values were estimated using the method of Bouwer and Rice (1976) for unconfined aquifers. The estimated values are reported in this appendix as Table C-1. Figures C-1 through C-4 include rising/falling head

curves showing assumed parameters used to estimate hydraulic conductivity values.

F:\docs\jobs\497852\BA3&4DataReport.doc

**Table C-1 - Hydraulic Conductivity Calculations for Wells in Unconfined Aquifer
Proposed Borrow Area 3**


	A3-B13-99	A3-B15-99	A3-B16-99	A3-B17-99
Well Depth in Feet	58	24	58	21.5
Screen Length in Feet	5	5	5	5
Depth to Screen in Feet	53	19	53	16.5
Depth to Aquitard in Feet	56.5	23	59	21.75
Depth to Water in Feet	53.04	18.28	47.04	17.6
Depth to Sandpack in Feet	51	17	50	14
H in Feet	3.46	4.72	11.96	4.15
n	0.3	0.3	0.3	0.3
r _c in Feet	0.083	0.083	0.167	0.083
r _w in Feet	0.333	0.333	0.500	0.333
r _{eff} in Feet	0.195	0.195	0.167	0.195
L _e in Feet	4.96	5	5	3.9
L _w in Feet	4.96	5.72	10.96	3.9
y1 in Feet	0.23	0.07	0.6	0.33
t1 in Seconds	10	20	0	0
y2 in Feet	0.01	0.001	0.001	0.062
t2 in Seconds	32	65	43.5	2500
L _{e/r_w}	14.88	15	10	11.7
A	2.0	2.0	1.8	1.9
B	0.3	0.3	0.3	0.3
C	1.4	1.4	1.2	1.3
Fully Penetrating Well				
ln(R _{e/r_w})	2.001	2.088	2.106	1.804
K in cm/s	3.3E-02	2.3E-02	2.6E-02	1.8E-04
	F-M SAND	Fine SAND	Med. SAND	Fine SAND

Notes:


Bold values to be entered manually.

A, B, and C coefficients are calculated using regression equations of Van Rooy, 1988.

Log of Normalized Drawdown vs. Time for A3-B13-99




Log of Normalized Drawdown vs. Time for A3-B15-99



J-4978-02 8/99
 Figure C-2

AR 052277


Log of Normalized Drawdown vs. Time for A3-B16-99



HARTCROWSER
 J-4978-02 8/99
 Figure C-3

AR 052278

Log of Normalized Drawdown vs. Time for A3-B17-99



HARTCROWSER
 J-4978-02 8/99
 Figure C-4

AR 052279



October 2, 2001

Ms. Ann Kenny
Washington Department of Ecology
Northwest Regional Office
3190 160th Avenue SE
Bellevue, WA 98008-5452

Re: Seattle-Tacoma International Airport
Washington Department of Ecology
§ 401 Water Quality Certification
Order #1996-4-02325
Condition F.1

Dear Ms. Kenny:

The Port of Seattle presents the attached documents to the Washington Department of Ecology in satisfaction of the above noted Order, Condition F.1. Condition F.1 requires, among other things, that the Port prepare "proposed construction BMPs to prevent interception of contaminated ground water by utility corridors and a plan to monitor potential contaminant transport to soil and ground water via subsurface utility lines".

Please review the two attached documents, *Proposed Construction BMPs To Prevent Interception of Contaminated Ground Water by Utility Corridors*, and *Plan to Monitor Potential Contaminant Transport to Soil and Ground Water via Subsurface Utility Lines*. If you have any questions or comments, please feel free to refer comments and questions to Paul Agid, 206-439-6604, agid.p@portseattle.org.

Sincerely,

A handwritten signature in cursive script that reads 'Elizabeth Leavitt'.

Elizabeth Leavitt
Manager, Aviation Environmental Programs

xc: Agid, Newlon

Seattle-Tacoma
International Airport
P.O. Box 68727
Seattle, WA 98168 U.S.A.
TELEX 703433
FAX (206) 431-5912

AR 052280



**Seattle Tacoma International Airport
§401 Water Quality Certification #1996-4-02325
Condition F.1**


**Proposed Construction BMPs
To Prevent Interception of Contaminated Ground Water by Utility Corridors**

In accordance with the Washington State Department of Ecology (Ecology) Water Quality Certification for U.S. Army Corps of Engineers Public Notice 1996-4-02325, Condition F. 1, the Port of Seattle (Port) submits this proposal for Best Management Practices (BMPs) for prevention of migration of contaminated ground water via subsurface utility lines at the Seattle-Tacoma International Airport (STIA). A draft of this BMP proposal is due to Ecology no later than September 30, 2001.

Best Management Practices for prevention of migration of contaminated ground water by newly constructed utility corridors will consist of, and will be implemented by modification of standard utility construction design guidelines and specifications. The following construction techniques will be specified for future construction of subsurface utilities below paved areas in the principal aviation operations and maintenance area (AOMA) of STIA. Subject subsurface utilities include, but are not limited to, electrical and communications ductbanks, and pipelines for carrying fuel, water, sanitary sewage, stormwater, and Industrial Waste System drainage.

1. Standard construction specifications will be developed for application to all construction projects located in areas within the AOMA where contaminated ground water is present at the designed construction depth.
2. The standard specification will include a requirement for the contractor to dewater utility trenches and other construction excavations that contain contaminated ground water, and to appropriately manage the water removed by disposal to an appropriately licensed facility or similar option.
3. The standard specification will include a requirement that utility backfill be constructed such that any ground water present at the utility depth not be transported along the utility, within the utility backfill material acting as a preferential flow pathway. The potential for transport in backfill will be minimized by use of construction techniques and/or materials that reduce utility backfill permeability. Generic engineering designs for preventing transport will be offered as examples, such as:
 - a. Construct backfill by placing controlled density fill (a lean concrete mixture), or similar low permeability material, into the entire utility trench, to the bottom of the pavement base course layer.
 - b. Construct backfill by placing standard pipe bedding material for a maximum depth of 6" plus one-half of the diameter of the utility pipe (except as noted below); backfill the remainder of the trench to the bottom of the pavement base course layer with controlled density fill or similar low permeability material; at a maximum interval of 500' along the utility alignment, eliminate the pipe bedding material and construct full trench profile concrete dams. (Illustrations of typical utility installation construction drawings consistent with option 3.b. are provided in Figure 1.)

Project-specific construction designs will be developed consistent with the standard specifications to meet the site-specific engineering requirements of the planned construction.




TYPICAL SECTION

TYPICAL ELECTRICAL/COMMUNICATION DUCTBANK
UNDER ALL PAVED AREAS
SCALE: NTS

GENERAL NOTE

UTILITY AND DUCTBANK BEDDING MATERIAL
ELIMINATED AT 500' INTERVALS AND REPLACED BY
FULL DEPTH CONCRETE OR CONTROL DENSITY FILL
(CDF) BARRIER.



TYPICAL SECTION

PIPE BEDDING AND TRENCH BACKFILL
UNDER ALL PAVED AREAS
SCALE: NTS

FIGURE 1
TYPICAL UTILITY
SECTIONS

Seattle Tacoma International Airport
§401 Water Quality Certification #1996-4-02325
Condition F.1

Plan to Monitor Potential Contaminant Transport to Soil and Ground Water
via Subsurface Utility Lines

1. INTRODUCTION AND BACKGROUND

In accordance with the Washington State Department of Ecology (Ecology) Water Quality Certification (WQC) for U.S. Army Corps of Engineers Public Notice 1996-4-02325, Condition F. 1, the Port of Seattle (Port) submits this plan to monitor for potential contaminant transport via subsurface utility lines (SULs) at the Seattle-Tacoma International Airport (STIA). A draft of this Subsurface Utility Line Monitoring Plan (SUL Monitoring Plan) is due to Ecology no later than September 30, 2001.

Ecology has requested this plan in response to concerns expressed by members of the public commenting on the proposed issuance of the Water Quality Certification. The commenter assert that the permeable backfill with which subsurface utilities are sometimes constructed may act as preferred pathways for migration of contaminated ground water to the Third Runway Embankment drain layer, and from the drain layer to area surface waters.

A related document, *Draft Technical Memorandum, Analysis of Preferential Ground Water Flow Paths Relative to Proposed Third Runway, Seattle-Tacoma International Airport*, prepared by Associated Earth Sciences, Inc. dated June 19, 2001 (AESI, 2001) provides the foundation and supporting data for the development of this SUL Monitoring Plan. The SUL Monitoring Plan presents a methodology to further evaluate the nature of SULs at appropriate contaminated ground water sites and the potential that these SULs act as preferential contaminant transport pathways. The planned monitoring approach will, in a first phase, evaluate contaminated sites, associated ground water presence and flow properties, and the properties of constructed SULs. The evaluation will demonstrate the probabilities that contaminated sites could act as contaminant sources to SULs, and that SULs could act as migration pathways for those contaminants. The second phase of the monitoring program will be developed at the conclusion of the first phase evaluation. Under the second phase, the Port will develop and implement field monitoring activities that are demonstrated appropriate by results of the first phase. The second phase plan will be provided to Ecology for review and approval.

2. SITE EVALUATION

a. Ground Water in Perched Zones and in the Qva Aquifer

The SUL Monitoring Plan will focus on the potential that select contaminated sites act as sources of contamination to SULs. The typical as-built construction depth of STIA SULs is between 5 to 10 feet below ground surface. The SUL Monitoring Plan will therefore concentrate on sites that contain impacted perched ground water that could enter SULs.

Sites that contain perched ground water provide the greatest probability for SUL transport of contamination. Perched ground water occurs in isolated, discontinuous zones. Perched zones are typically found within the range of about 10 – 35 feet below ground surface. Due to the shallow depth of perched zones, perched ground water has the greatest potential to intersect SULs and move along permeable backfill material

Transport along SUL backfill of contaminated ground water in the regional Qva aquifer is improbable for several reasons:

- Ground water levels in the Qva aquifer at STIA are typically at a depth between 55 to 90 feet below ground surface, which is well below the depth of typical SULs.
- Impacted Qva ground water has been well documented and is contained within the AOMA; the maximum migration of impacted ground water is no greater than 550 feet in length from its contaminant source area.
- Ground water data generated from monitoring wells completed downgradient from known Qva impacted ground water sites are below Model Toxics Control Act (MTCA) standards and, therefore, provide a defined plume boundary.

Therefore, monitoring for contaminant transport by SULs in the Qva aquifer is not planned.

b. SUL Monitoring Plan Site Selection

Locations with contaminated ground water that may have a reasonable potential for migration by SUL are defined by the following criteria:

- Site contains perched ground water;
- Perched ground water is impacted above MTCA standards;
- SULs intersect the site footprint.

Data indicate that five sites within the STIA principal aviation operations and maintenance area (AOMA) contain impacted perched ground water that has exceeded MTCA Method A or Method B clean up standards (AESI, 2001). Sites that are impacted by previous fuel releases and contain fuel related compounds in the perched ground water system elevated above MTCA standards include the United/Continental Fuel Farm, Pan Am Avgas Tanks, Northwest Airlines Bulk Fuel Farm, and the Delta Auto Gas Cluster. In addition two areas in the AOMA, the Northwest Airlines Former Hangar Tanks and Monitoring well AGC-5 at the Delta Autogas Cluster site, represent areas that contain solvent impacted perched ground water. Each of the five sites meets the criteria listed above and are proposed for further detailed evaluation regarding shallow contaminant transport mechanisms via SULs.

3. SUBSURFACE UTILITY LINE INFORMATION

As part of previous evaluations, SULs have been identified throughout STIA and compiled on a base map (AESI, 2001). SULs that have been identified include: existing and proposed fuel lines, electric lines, Industrial Waste System (IWS) lines, sewer lines, storm drains, water lines, and Satellite Transit System (STS) and Baggage Tunnels. A number of these SULs are constructed within the boundaries of impacted perched ground water of the five sites presented in Section 2. The following additional detail will be compiled from available documentation for SULs at each of the subject sites.

- Utility line depth – Typical utility depth is 5 to 10 feet below ground surface, with a typical maximum depth of 20 feet below ground surface. Engineering drawings will be researched to identify the as-built construction depth of each SUL intersecting the subject sites.
- Utility line backfill composition – Information on the type of backfill material used for infill of the SUL will be compiled, if available.
- Utility line excavation slope – The elevation of the as-built SUL excavation will be researched and information compiled, if available.

- d. **Construction Observations** - Records will be researched to determine if observations were recorded during construction activities regarding soil or ground water contamination, saturated soil conditions, soil type, SUL condition, etc. Observations of recent capital improvement construction projects (e.g., those associated with the South Terminal Expansion Project (STEP)) will provide useful information regarding observed subsurface conditions in the vicinity of historic contaminated sites and older SULs. Available information will be summarized for each subject site.

4. GEOLOGIC/GROUND WATER CONDITIONS

Existing data and field observations of the geologic and ground water conditions at each of the subject sites will be evaluated in detail in regards to its influence on potential contaminant migration pathways. Cross sections will be developed for each site to graphically depict the relationship of geologic and ground water conditions in relationship to SULs. The analysis will focus on the following elements:

- a. **Fill or Native Soil Types in Relation to Utility Line** – The soil conditions surrounding SULs at each site will be evaluated. Interpretations will be developed based on surrounding soil borings and well logs regarding the nature of fill or native soil types. This information will be evaluated in relation to the as-built construction depth of the SULs.
- b. **Slope of Till or Impervious Surface** – The slope of the glacial till surface or any identified impervious surface will be evaluated. The effect of the slope of the low permeability surface will be analyzed regarding its effect on the control of perched ground water flow directions.
- c. **Depth to Perched Ground Water** – The depth to perched ground water will be compiled from shallow monitoring well water level data and observations made on associated environmental and soil boring logs. This data will be correlated to a common vertical datum to allow for the calculation of the elevation of the ground water surface.
- d. **Perched Ground Water Flow Direction** – For each site evaluated, the perched ground water flow directions will be determined and a contour map showing the flow directions will be developed. Typical wet season and dry season perched ground water elevations will be used to determine any change in flow direction as a result of seasonal precipitation fluctuations.
- e. **Relationship of Perched Ground Water to Utility Line Excavation** – The depth to perched ground water will be compared to the as-built excavation depth of various SULs intersecting subject sites. An evaluation will be made concerning the ability of the SULs to act as a potential contaminant transport pathway. Particular consideration will be made during the evaluation of the ability of the SULs to transport contaminant via perched ground water towards the proposed Third Runway Embankment project area.

5. Report

A report will be developed which presents the findings outlined in the SUL Monitoring Plan. The report will present graphical maps which show ground water and geological conditions in relation to SULs, tabulated information on select SULs, and an evaluation regarding the potential of the SULs to act as preferential pathways for contaminant transport. Conclusions will be developed and an appropriate scope of work and work plan for any appropriate follow-on monitoring will be developed for Ecology review and approval.